



# LUBRICANTS

April 8, 2011

Re: Update from **BRAD PENN**<sup>®</sup> Technical Services Department

Dear **BRAD PENN**<sup>®</sup> Distributor:

Our commitment in keeping our distributors informed with news regarding the **BRAD PENN**<sup>®</sup> product line is the foundation of this letter. The **BRAD PENN**<sup>®</sup> **MULTI-VEHICLE ATF (#7423)** Product Data Sheet (PDA) and associated Media material has been upgraded with additional OEM specification data. Please refer to the new highlighted material below:

**BRAD PENN**<sup>®</sup> **MULTI-VEHICLE ATF** is approved for use in Allison C-4, Ford Mercon<sup>®</sup> V, JASO 1-A, Voith 55.6335.XX (G607) and Volvo 97340 applications.

The **BRAD PENN**<sup>®</sup> **MULTI-VEHICLE ATF** is suitable for use in the following:

Aisin Warner AW-1*	MAN 339 Z1
Audi G 052 162 / Audi G 052 990	Mazda ATF-M III
Audi G 055 025	Mazda ATF-MV
BMW 7045E	Mercedes Benz 236.1 / 236.2 / 236.3 /236.5 / 236.6 / 236.7 / 236.9 / 236.10 /236.11
BMW LA2634 BMW LT 71141	Mitsubishi SP-II, SP-III
Chrysler ATF's	Mitsubishi ATF J2*
Chrysler Mopar AS68RC	Nissan 402
DEXRON <sup>®</sup>	Nissan Matic-D, J, K
DEXRON <sup>®</sup> -II	Nissan Matic-S*
DEXRON <sup>®</sup> -IID / IIE	Shell 3403
DEXRON <sup>®</sup> -IIIF / IIIG	Shell LA2634
DEXRON <sup>®</sup> -IIIH	Subaru ATF, ATF-HP
DEXRON <sup>®</sup> VI*	Suzuki 3314 & 3317
Esso LT 71141	Texaco ETL-7045E / ETL-8072B
Ford FNR5	Texaco N402
Ford Mercon <sup>®</sup>	Toyota T-III
Honda ATF-Z1	Toyota T-IV
Hyundai/Kia SP-II & SP-III / JWS 3314, JWS 3317	Toyota WS (JWS 3324)*
Hyundai NWS-9638*	Volvo Pass. Car (4-6 sp)
Kia Red-1	Volvo 97341
Idemitsu K17	VW G 052 162
JWS 3309, 3314, 3317	VW G 052 990
JWS 3324*	VW G 055 025
MAN 339F	ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C
MAN 339 V1	

\* Viscosity Requirement Not Met



**BRAD PENN® MULTI-VEHICLE ATF** is not recommended for the following applications:

Allison TES-295 Allison TES-389	Mercedes Benz 236.8 / 236.12* / 236.14* /236.15*
Ford Type F	Mitsubishi SP-IV
Ford Mercon® SP	Saab 93 165 147
Ford Mercon® LV	Shell M-1375.4
Honda DW -1*	Voith 55.6336.XX (G1363)
Hyundai/Kia SP-IV	ZF TE-ML 14B
MAN 339 V2	ZF TE-ML 14C
MAN 339 Z2	CVT / Continuously Variable Transmission
MAN 339 Z3	DCT / Dual Clutch Transmission

\* Viscosity Requirement Not Met

All “approved” and “suitable for use” specifications listed would qualify as suitable for complete fluid drain/replacement. The specifications “not recommended” are self-explanatory.

It remains imperative that you continue to instruct your customers to always consult the equipment owner’s manual for proper fluid selection. Should you have any questions regarding this information, please contact your Regional Sales Manager or **BRAD PENN®** Technical Services Department.

Kenneth M. Tyger, OMA I, OMA II  
Oil Monitoring Analyst  
Sr. Technical Services Representative  
American Refining Group, Inc.  
77 North Kendall Ave.  
Bradford, Pa. 16701  
(814)-368-1210  
ktyger@amref.com