



Product Bulletin

PENN-GRADE 1[®] BREAK-IN OIL

BRAD PENN[®] PENN GRADE 1[®] BREAK-IN OIL provides wear control for critical engine parts while allowing the engine components to seat, resulting in maximum engine performance and life. It is formulated with Penn Grade Base Stocks and a state-of-the-art additive system, available in SAE 30.

BRAD PENN[®] PENN GRADE 1[®] BREAK-IN OIL is an optimum choice for professional engine builders.

BRAD PENN[®]

PENN GRADE 1[®] BREAK-IN OIL- Typical Properties

SAE Grade		30
API Gravity, 60°F	ASTM D-1298A	27.8
Density, lbs/gal (g/L)	Calculated	7.398 (888.3)
Viscosity, cSt @ 40°C	ASTM D-445	93.3
Viscosity, cSt @ 100°C	ASTM D-445	11.3
Viscosity, SUS @ 100°F	ASTM D-2161	432.5
Viscosity, SUS @ 210°F	ASTM D-2161	66
Viscosity Index	ASTM D-2270	107.0
Pour Point, °F (°C)	ASTM D-97	-30 (-33)
Flash Point, COC, °F (°C)	ASTM D-92	440(226)
Color		Green
TBN	ASTM D-2896	7.2
Sulfated Ash, mass %	ASTM D-874	0.95
Product Code		7120



AMERICAN REFINING GROUP, INC.

77 North Kendall Avenue • Bradford, Pennsylvania • 16701

Phone: 814.368.1200 • Fax 814.368.1219 • www.amref.com • ISO 9001:2008