



# Product Bulletin

## BRAD PENN<sup>®</sup> RED 000 LITHIUM EP GREASE

**BRAD PENN<sup>®</sup> Red 000 Lithium EP Grease** is formulated with high quality base stocks, additives and thickeners. It is particularly suited for use in the lubrication of gears in gear cases and other industrial applications where leakage is a problem, it is designed to stay in place and provide dependable EP lubrication where conventional heavy viscosity gear oils will not in turn reducing consumption.

### BRAD PENN<sup>®</sup> Red 000 Lithium EP Grease

#### Typical Properties

NLGI Grade	Test Method	000
Color		Dark Red
Appearance		Smooth
Thickener Type (soap)		Lithium 12 Hydroxy
Thickener Content, wt.%	ASTM D-128	1-3
Cone penetration @77°F, worked 60 strokes	ASTM D-217	445-475
Dropping Point, °F (°C)	ASTM D-2265	NA
Base Oil Viscosity, cSt @ 40°C cSt @ 100°C	ASTM D-445	300-350 24
Viscosity Index (min)	ASTM D-2270	90
Water Spray Off, wt.% loss	ASTM D-4049	2.5
Four-Ball Weld Point, kgf (min)	ASTM D-2596	200
Operating Temperature Ranges Minimum, °F (°C) Maximum Continuous Service, °F (°C)		0 (-18) 300 (149)
Timken OK Load, lbs	ASTM D-2509	35
<b>Product Code</b>		<b>7866</b>



**AMERICAN REFINING GROUP, INC.**

77 North Kendall Avenue • Bradford, Pennsylvania • 16701

Phone: 814.368.1200 • Fax 814.368.1219 • [www.amref.com](http://www.amref.com) • ISO 9001:2008