

## Material Safety Data Sheet

Prepared according to 29 CFR 1910.1200

### 1. Chemical Product and Company Identification

American Refining Group, Inc.  
77 North Kendall Avenue  
Bradford, PA 16701 USA  
Tel: (814) 368.1200  
www.amref.com



<b>Product Name</b>	Kensol 30
<b>Product Code</b>	4111
<b>CAS Number</b>	8052-41-3
<b>Synonyms</b>	Naphtha, stoddard Solvent, mineral spirits, white spirit
<b>Generic Chemical Name</b>	Naphtha, high paraffinic, stoddard solvent
<b>Product Type</b>	Substance
<b>Transportation Emergency Phone No.</b>	Chemtrec: 1-800-424-9300 (24 HRS)
<b>ARG Emergency Phone No.</b>	814-368-1297 (24 HRS)
<b>MSDS E-Mail</b>	msds@amref.com

### 2. Hazards Identification

<b>Appearance</b>	Colorless liquid
<b>Odor</b>	Hydrocarbon oil
<b>Signal Word</b>	WARNING! Flammable liquid and vapor (may cause explosion) Static accumulating liquid can become electrostatically charged even in bonded and grounded equipment; Sparks may ignite liquid and vapor may cause flash fire (or explosion) Harmful if swallowed. Can enter lungs and cause damage Harmful if inhaled May cause internal organ effects based on chronic studies with laboratory animals May cause skin irritation Prolonged skin contact may cause irritation May cause eye irritation May cause respiratory tract irritation
<b>Exposure Routes</b>	Target Organs: eyes, skin, respiratory system, central nervous system, kidneys Inhalation, ingestion, skin and/or eye contact
<b>OSHA Regulatory Status</b>	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)
<b>Precautions</b>	Keep away from heat, sparks and flame. Keep container tightly closed. Use only with adequate ventilation. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity.

**2. Hazards Identification**

<b>Inhalation</b>	Avoid breathing dust/fume/gas/mist/vapors/spray. Keep container tightly closed. Use only with adequate ventilation.
<b>Eyes</b>	Avoid contact with eyes. Wash thoroughly after handling.
<b>Skin</b>	Avoid contact with skin and clothing. Wash thoroughly after handling.
<b>Symptoms of Exposure</b>	Irritation eyes, nose, throat; dizziness; dermatitis; chemical pneumonitis (aspiration liquid); in animals: kidney damage
<b>Medical Conditions Aggravated by Exposure</b>	Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product
<b>Chronic Effects</b>	See Section 11 for complete health hazard information
<b>Environmental Effects</b>	See Section 12 for complete ecological information

**3. Composition / Information on Ingredients**

CAS No.	Component	Percent
8052-41-3	Stoddard solvent	100

Component Regulatory Information      This product may be regulated, have exposure limits or other information identified as the following: Stoddard solvent (See Section 8)

**4. First Aid Measures**

<b>Eyes</b>	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
<b>Skin</b>	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
<b>Inhalation</b>	Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
<b>Ingestion</b>	DO NOT INDUCE VOMITING. If conscious, rinse out mouth with water. Get medical attention immediately.
<b>Note to Physicians</b>	No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

## 5. Fire Fighting Measures

### Flammable Properties

This product is a static accumulating liquid. Static accumulating liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor may cause flash fire. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Restrict flow velocity to avoid build-up of static charge. Refer to NFPA 77, API 2003, and CENELEC CLC/TR 50404 for further guidance.

### Extinguishing Media

Use dry chemical, CO<sub>2</sub>, water spray (FOG) or foam

### Specific Hazards Arising from Chemical

Elevated temperatures can lead to the formation of irritating fumes and vapors. Decomposition products may include the following materials: Carbon dioxide and Carbon monoxide.

### Protective Equipment and Precautions for Firefighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. Accidental Release Measures

### Personal Precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

### Environmental Precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution.

### Methods for Containment

Stop leak if without risk.

### Methods for Cleanup

Move containers from spill area. Approach release from upwind. Absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## 7. Handling and Storage

### Handling Procedures

Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Use non-sparking tools.

### Shipping and Storing Procedures

Store in accordance with local regulations. Store in a segregated and approved area. Keep in the original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials. Do not store in unlabeled containers. Store and use away from heat, sparks, open flame or any other ignition source. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers that retain product residue may be hazardous. Do not reuse container.

## 8. Exposure Controls / Personal Protection

**8. Exposure Controls / Personal Protection**

**Component Exposure Limits**

**Stoddard Solvent**

<b>ACGIH TLV:</b>	TWA: 100 ppm	TWA: N/A mg/m <sup>3</sup>	STEL: N/A ppm	STEL: N/A mg/m <sup>3</sup>
<b>OSHA PEL:</b>	TWA: 500 ppm	TWA 2900 mg/m <sup>3</sup>	STEL: N/A ppm	STEL: N/A mg/m <sup>3</sup>
<b>NIOSH REL:</b>	TWA: N/A ppm	TWA 350 mg/m <sup>3</sup>	STEL: N/A ppm	STEL: N/A mg/m <sup>3</sup>
<b>NIOSH Ceiling:</b>	1800 mg/m <sup>3</sup> [15 minute]			

N/A signifies not available

**Engineering Controls**

This product is a static accumulating liquid. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Material should be handled in enclosed vessels and equipment. Use only in adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Eye/Face Protection**

Chemical goggles or face shield.

**Skin Protection**

Chemical resistant, impervious gloves complying with an approved standard should be worn at all times. Coveralls, apron, and boots as necessary to minimize contact.

**Respiratory Protection**

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicated this is necessary. Respirator selection must be based on known or anticipated exposure levels.

**General Hygiene**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing.

**9. Physical and Chemical Properties**

<b>Appearance</b>	Colorless	<b>Vapor Pressure (mm Hg at 20°C)</b>	0
<b>Odor</b>	Hydrocarbon oil	<b>Water Soluble</b>	No
<b>Physical State</b>	Liquid	<b>Specific Gravity (g/cc)</b>	.774
<b>Flash Point (°F)</b>	105	<b>Density (lbs/gal)</b>	6.43
<b>Boiling Point (°F)</b>	>310	<b>pH</b>	Not available

**10. Chemical Stability & Reactivity Information**

**Stability**

Stable under normal conditions. If heated, product's static accumulation will rise and could cause flash fire.

**Polymerization**

No polymerization

**Incompatibility**

Strong acids and oxidizing materials

**Conditions to Avoid**

High temperatures, sparks, flames

**Hazardous Decomposition**

Smoke, carbon monoxide, carbon dioxide, aldehydes and other products of incomplete combustion.

**Products**

## 11. Toxicological Information

<b>Acute Exposure</b>	
<b>Respiratory Irritation</b>	Aspiration and inhalation hazard. If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract. Based on data from components or similar materials.
<b>Eye Irritation</b>	May cause eye irritation. Vapors formed from heating may cause eye irritation.
<b>Skin Irritation</b>	Can cause skin irritation. Prolonged or repeated direct exposure to the skin results in symptoms of irritation and redness, dermatitis or oil acne.
<b>Sensitization</b>	Not expected to cause skin or respiratory sensitization.

### Component Analysis – LD50 / LC50

#### Acute Toxicity Estimate (ATE) Values for Product:

<b>Inhalation LC50 Rat</b>	>20 mg/L 1 HR
<b>Oral LD50 Rat</b>	>7000 mg/kg
<b>Dermal LD50 Rabbit</b>	>2000 mg/kg

<b>Chronic Exposure</b>	
<b>Target Organ Effects</b>	Repeated-dose dermal and inhalation studies in rats using similar substances revealed an internal organ effect (i.e., adrenal enlargement) that was reversible after 4 weeks.
<b>Carcinogenicity</b>	No data available to indicate product or any components present at greater than .1% are carcinogenic.
<b>Mutagenicity</b>	No data available to indicate product or any components present at greater than .1% are mutagenic or genotoxic.
<b>Reproductive Toxicity</b>	No data available to indicate either product or components present at greater than .1% that may cause reproductive toxicity.
<b>Teratogenicity</b>	No data available to indicate product or any components contained at greater than .1% may cause birth defects.

## 12. Ecological Information

### Component Analysis- Ecotoxicity – Aquatic Life

Duration/Test/Species	Concentration/Conditions
96 Hr LC50 Pimephales promelas	N/A mg/L

<b>Degradability</b>	Not determined
<b>Bioaccumulation</b>	Not determined
<b>Soil Mobility</b>	Not determined


## 13. Disposal Considerations

**13. Disposal Considerations**

**Disposal Instructions**

The generation of waste should be avoided or minimized wherever possible. Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

**14. Transportation Information**

14. Transportation Information					
Emergency Response Guide No.		128		North American Emergency Response Guide Book	
	NA Number	Shipping Name (technical name)	Hazard Class	Packing Group	Labels/Placard*
<b>U.S. DOT Bulk (over 119 gallons)</b>	1993	Combustible liquid N.O.S. (stoddard solvent)	combustible liquid	III	 <p>Bulk container must be labeled on two opposing sides</p>
<b>U.S. DOT Non-Bulk (under 119 gallons)</b>		Not regulated			Exempt from labeling and placarding unless shipped via Air or Vessel

\*Truck/Rail car must be placarded if aggregate gross weight exceeds 1,000 pounds

**15. Regulatory Information**

**SARA Extremely Hazardous Substances (Sections 302 & 304)**

This product does not contain greater than 1% of any “extremely hazardous substances” listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

**SARA Section 313**

This product does not contain greater than 1.0% of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

**SARA Section 311 & 312 Classifications**

**Acute Hazard** Yes  
**Chronic Hazard** Yes  
**Fire Hazard** Yes  
**Reactivity Hazard** Yes

**CERCLA**

This product does not contain any “hazardous substances” listed under the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

**California Prop 65**

This product contains chemical(s) known to the state of California to cause cancer and/or birth defects.

**Clean Water Act / Oil Pollution Act**

This product may be subject to regulation by Section 311 of the Clean Water Act and the Oil Pollution Act. Releases of the product into or leading to surface waters must be reported to the National Response Center at 1-800-424-8802.

**Global Chemical Inventories**

<b>Inventory</b>	<b>Component</b>
	<b>All components</b>
US TSCA	Present
EU	Present
Japan	Not available
Australia	Present
New Zealand	Present
Canada	Present
Switzerland	Not available
Korea	Present
Philippines	Present
China	Present
Taiwan	Not available

**16. Other Information**

**US NFPA Ratings**

<b>Health</b>	<b>Fire</b>	<b>Instability</b>
2	2	1

**HMIS Ratings**

<b>Health</b>	<b>Fire</b>	<b>Physical Hazards</b>
2*	2	1

**Precautionary Labels**

**Signal Word**

**WARNING!**

Flammable liquid and vapor (may cause explosion)  
 Static accumulating liquid can become electrostatically charged even in bonded and grounded equipment; Sparks may ignite liquid and vapor may cause flash fire (or explosion)  
 Harmful if swallowed. Can enter lungs and cause damage  
 Harmful if inhaled  
 May cause internal organ effects based on chronic studies with laboratory animals  
 May cause skin irritation  
 Prolonged skin contact may cause irritation  
 May cause eye irritation  
 May cause respiratory tract irritation

**16. Other Information**

Target Organs: eyes, skin, respiratory system, central nervous system, kidneys

**Preparation/Revision Date**

1/24/2012

**Revision Reason**

Outdated

**Prepared By:**

Jenna Prechtel, Product Compliance Coordinator

*The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.*

**End of MSDS**