

# KENSOL®

## SPECIALITY SOLVENTS

### CONVENTIONAL GASOLINE

(PREMIUM 93 OCTANE, 68955-35-1)

**Category:** FUELS (WINTER)

**Generic Name:** 93 OCTANE PREMIUM GASOLINE

**Description:** 93 OCTANE UNLEADED GASOLINE WITH DETERGENT ADDITIVE

**Applications:** FUEL FOR GASOLINE ENGINES

**Product Code:** B10-5014

**SPECIFICATIONS APPLICABLE FOR:** NOV 1 TO MAR 31

ASTM METHOD	DESCRIPTION	TYPICAL VALUE	SPECIFICATION		
			MIN		MAX
D-130	SILVER CORROSION				1.0
D-130	COPPER STRIP CORROSION				1.0
D-381	EXISTENT GUM, mg/100mL				5.0
D-525	OXIDATION STABILITY, MINUTES		240.0		
D-2699/D-2700	(R+M)/2 - ANTI-KNOCK INDEX		93.0		
D-2622	SULFUR , MASS %				0.0030
D-3237	LEAD CONTENT, g/gal				0.05
D-3231	PHOSPHORUS CONTENT, g/gal				0.005
D-86	DISTILLATION, °F				
	10% EVAPORATED, °F				122
	50% EVAPORATED, °F		150		230
	90% EVAPORATED, °F				365
	END POINT, °F				437
	RESIDUE, VOL%				2
D-5191	VAPOR PRESSURE, psi				15.0
D-5188	T V/L=20, °F		105		
D-4814, Table 1	DRIVEABILITY INDEX, °F				1200

Rev. 1/19/10

THE CHEMICAL, PHYSICAL, AND PHYSIOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN FULLY INVESTIGATED AND ITS HANDLING, MIXING WITH INCOMPATIBLE CHEMICALS OR USE MAY BE HAZARDOUS. THIS PRODUCT IS FOR INDUSTRIAL USE ONLY. DO NOT INGEST. KEEP AWAY FROM CHILDREN. MATERIAL SAFETY DATA SHEETS ARE AVAILABLE UPON REQUEST.

NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING PATENT WARRANTIES, OR WARRANTIES OF MERCHANTABILITY OF FITNESS FOR USE, ARE MADE BY AMERICAN REFINING GROUP, INCORPORATED WITH RESPECT TO PRODUCTS DESCRIBED OR INFORMATION SET FORTH HEREIN, NOTHING CONTAINED HEREIN SHALL CONSTITUTE A PERMISSION OR RECOMMENDATION TO PRACTICE ANY INVENTION COVERED BY A PATENT WITHOUT A LICENSE FROM THE OWNER OF THE PATENT.



ARB101 (5/02)

77 North Kendall Avenue • Bradford, Pennsylvania • 16701 • Phone: 814.368.1200  
Fax 814.368.4563 • e-mail: arg@amref.com • [www.amref.com](http://www.amref.com) • ISO 9001:2008