

# KENSOL®

## INDUSTRIAL PRODUCTS

### E10 GASOLINE (87 OCTANE)

(C.A.S. 64-17-5 & 68955-35-1)

<b>Category:</b>	FUELS (SPRING / FALL)			
<b>Generic Name:</b>	87 OCTANE GASOLINE, E10 GASOLINE			
<b>Product Code:</b>	B10-5020			
<b>SPECIFICATIONS APPLICABLE FOR:</b>	APR 1 TO APR 30		SEPT 16 TO OCT 31	
ASTM METHOD	DESCRIPTION	TYPICAL VALUE	SPECIFICATION	
			MIN	MAX
D-130	SILVER CORROSION			1.0
D-130	COPPER STRIP CORROSION			1.0
D-381	EXISTENT GUM, mg/100mL			5.0
D-525	OXIDATION STABILITY, MINUTES		240.0	
D-2699	RESEARCH OCTANE NUMBER		TEST	
D-2700	MOTOR OCTANE NUMBER		TEST	
	R+M/2		87.0	
D-2420	H2S	NEG		
D-2622	SULFUR , MASS %			0.0030
D-7039	SULFUR, mg/kg			30.0
	COLOR, VISUAL	UNDYED		
D-3237	LEAD CONTENT, g/U.S. gallon			0.05
D-3231	PHOSPHORUS CONTENT, g/U.S. gallon			0.005
D-4952	DOCTORS TEST	SWEET		
D-6729 or E168	ETHANOL CONTENT (VOLUME %)	9.7	9	10.0
D-86	DISTILLATION, °F			
	10% EVAPORATED, °F			131
	50% EVAPORATED, °F		150	235
	90% EVAPORATED, °F			365
	END POINT, °F			437
D-5188	T v/L = 20, °F		116	
D-5191	VAPOR PRESSURE, psi			13.5
D-4814, Table 1	DRIVEABILITY INDEX, °F			1220
				Rev. 3/10/11

THE CHEMICAL, PHYSICAL, AND PHYSIOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN FULLY INVESTIGATED AND ITS HANDLING, MIXING WITH INCOMPATIBLE CHEMICALS OR USE MAY BE HAZARDOUS. THIS PRODUCT IS FOR INDUSTRIAL USE ONLY. DO NOT INGEST. KEEP AWAY FROM CHILDREN. MATERIAL SAFETY DATA SHEETS ARE AVAILABLE ON REQUEST.

NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING PATENT WARRANTIES, OR WARRANTIES OF MERCHANTABILITY OF FITNESS FOR USE, ARE MADE BY AMERICAN REFINING GROUP, INCORPORATED WITH RESPECT TO PRODUCTS DESCRIBED OR INFORMATION SET FORTH HEREIN, NOTHING CONTAINED HEREIN SHALL CONSTITUTE A PERMISSION OR RECOMMENDATION TO PRACTICE ANY INVENTION COVERED BY A PATENT WITHOUT A LICENSE FROM THE OWNER OF THE PATENT.

