KENSOL®

INDUSTRIAL PRODUCTS

KENSOL® K-1

(C.A.S. 8008-20-6)

Category:	DISTILLATE
Generic Name:	K-1 KEROSENE
Description:	LOW SULFUR KEROSENE (<400 PPM SULFUR)
Applications:	FUEL FOR HEATERS
Product Code:	D10-4112

ASTM METHOD	DESCRIPTION	TYPICAL VALUE	SPECIFICATION MIN		MAX
	LB/GAL	6.56			
D-4052	GRAVITY, API	48.0	47.0		49.5
D-445	VISCOSITY @ 40ºC, cSt	1.5	1.0		1.9
D-2161	VISCOSITY @ 100ºF, SUS	31.2			
D-56	FLASH POINT, ºC (TCC)		38		
D-156	COLOR, SAYBOLT		+16		
D-86	DISTILLATION, ºF				
	10%	365			401
	EBP	471			572
D-130	COPPER STRIP CORROSION	1B			3
D-5773	CLOUD POINT, ºC	-39			
D-2386	FREEZING POINT, ºC				-30
D-2622	SULFUR % WT	<0.0010			0.0030
D-3227	MERCAPTAN SULFUR CONTENT, PPM				30

Rev. 4/27/10

THE CHEMICAL, PHYSICAL, AND PHYSIOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN FULLY INVESTIGATED AND ITS HANDLING, MIXING WITH INCOMPATIBLE CHEMICALS OR USE MAY BE HAZARDOUS. THIS PRODUCT IS FOR INDUSTRIAL USE ONLY. DO NO INGEST. KEEP AWAY FROM CHILDREN. MATERIAL SAFETY DATA SHEETS ARE AVAILABLE ON REQUSET.

NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING PATENT WARRANTIES, OR WARRANTIES OF MERCHANTABILITY OF FITNESS FOR USE, ARE MADE BY AMERICAN REFINING GROUP, INCORPORATED WITH RESPECT TO PRODUCTS DESCRIBED OR INFORMATION SET FORTH HEREIN, NOTHING CONTAINED HEREIN SHALL CONSTITUTE A PERMISSION OR RECOMMENDATION TO PRACTICE ANY INVENTION COVERED BY A PATENT WITHOUT A LICENSE FROM THE OWNER OF THE PATENT.

AMERICAN REFINING GROUP, INC.

77 North Kendall Ave. • Bradford, PA • 16701 • Phone: 814.368.1200
Fax 814.368.4563 • e-mail:arg@amref.com • www.amref.com