

# KENSOL®

## SPECIALITY SOLVENTS

### GRADE NO. 2 DIESEL S-500 DYED (DEC-FEB)

(C.A.S. 68476-34-6)

**Category:** FUELS

**Generic Name:** DYED LOW SULFUR DIESEL, OFF-ROAD DIESEL

**Description:** LOW SULFUR #2 DIESEL FUEL - DYED

**Applications:** LOW SULFUR FUEL FOR DIESEL ENGINES

**Product Code:** D10-8106

#### SPECIFICATIONS FOR DECEMBER, JANUARY & FEBRUARY

ASTM METHOD	DESCRIPTION	TYPICAL VALUE	SPECIFICATION		
			MIN		MAX
D-4052	GRAVITY, °API		30.0		
D-445	VISCOSITY @ 40°C, cSt		1.7		4.1
D-93	FLASH POINT, °F (Pensky Marten)	138	100		
D-2622	SULFUR, WT %				0.05
D-7039	SULFUR, mg/Kg				500
D-5773	CLOUD POINT, °C				-15
D-4737	CETANE INDEX (CALCULATED)		40		
	COLOR DYED	RED			
D-86	DISTILLATION, °F 90%(FROM D-975)		WAIVED		
D-130	COPPER STRIP CORR., 3 HRS @ 122°	1b			3.0
D-482	ASH, MASS %				0.01
D-2709	WATER AND SEDIMENT, VOL %				0.05
D-524	RAMSBOTTOM CARBON, % Mass				0.35
D-2624	CONDUCTIVITY, pS/m (C.U.)		25		
D-6304	KF MOISTURE, ppm				100
Method 15	VISUAL INSPECTION		CLEAR & BRIGHT		
					Rev. 1/20/10

THE CHEMICAL, PHYSICAL, AND PHYSIOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN FULLY INVESTIGATED AND ITS HANDLING, MIXING WITH INCOMPATIBLE CHEMICALS OR USE MAY BE HAZARDOUS. THIS PRODUCT IS FOR INDUSTRIAL USE ONLY. DO NOT INGEST. KEEP AWAY FROM CHILDREN. MATERIAL SAFETY DATA SHEETS ARE AVAILABLE UPON REQUEST.

NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING PATENT WARRANTIES, OR WARRANTIES OF MERCHANTABILITY OF FITNESS FOR USE, ARE MADE BY AMERICAN REFINING GROUP, INCORPORATED WITH RESPECT TO PRODUCTS DESCRIBED OR INFORMATION SET FORTH HEREIN, NOTHING CONTAINED HEREIN SHALL CONSTITUTE A PERMISSION OR RECOMMENDATION TO PRACTICE ANY INVENTION COVERED BY A PATENT WITHOUT A LICENSE FROM THE OWNER OF THE PATENT.



ARB101 (5/02)

77 North Kendall Avenue • Bradford, Pennsylvania • 16701 • Phone: 814.368.1200  
Fax 814.368.4563 • e-mail: arg@amref.com • [www.amref.com](http://www.amref.com) • ISO 9001:2008