KENSOL®

INDUSTRIAL PRODUCTS

GRADE NO.2 DIESEL S-500 DYED L-M (MAR-NOV)

(C.A.S. 68476-34-6)

Category: FUELS

Generic Name: #2 LOCOMOTIVE - MARINE (MARCH-NOVEMBER)

Product Code: D10-8150

ASTM METHOD	DESCRIPTION	TYPICAL VALUE	SPECIFICATION MIN		MAX
D-4052	GRAVITY, API		30.0		
D-93	FLASH, PMCC, ºF		125		
D-445	VISCOSITY @ 40 ºC, cSt		1.9		4.1
D-130	COPPER STRIP CORROS.,3Hrs@122ºF				3.0
D-2622	SULFUR, % WT				0.05
D-7039	SULFUR, mg/Kg				500
D-482	ASH, % Mass				0.01
D-524	RAMSBOTTOM CARBON, % Mass				0.35
D-5773	CLOUD POINT, ºC				
	MARCH - APRIL 15TH				-9
	APRIL 16 - OCTOBER				3
	NOVEMBER				-9
D-2709	WATER & SEDIMENT, Vol. %				0.05
D-4737	CETANE INDEX (CALCULATED)		40		
D-2624	CONDUCTIVITY, pS/m (C.U.)		25		
D-6304	KF MOISTURE, ppm				100
Method 15	VISUAL INSPECTION	CLEAR & BRIGHT			
	COLOR (DYED)		RED		
D-86	DISTILLATION, ºF				
	90% (FROM D-975)		540		640

Rev. 3/25/10

THE CHEMICAL, PHYSICAL, AND PHYSIOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN FULLY INVESTIGATED AND ITS HANDLING, MIXING WITH INCOMPATIBLE CHEMICALS OR USE MAY BE HAZARDOUS. THIS PRODUCT IS FOR INDUSTRIAL USE ONLY. DO NO INGEST. KEEP AWAY FROM CHILDREN. MATERIAL SAFETY DATA SHEETS ARE AVAILABLE ON REQUSET.

NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING PATENT WARRANTIES, OR WARRANTIES OF MERCHANTABILITY OF FITNESS FOR USE, ARE MADE BY AMERICAN REFINING GROUP, INCORPORATED WITH RESPECT TO PRODUCTS DESCRIBED OR INFORMATION SET FORTH HEREIN, NOTHING CONTAINED HEREIN SHALL CONSTITUTE A PERMISSION OR RECOMMENDATION TO PRACTICE ANY INVENTION COVERED BY A PATENT WITHOUT A LICENSE FROM THE OWNER OF THE PATENT.

AMERICAN REFINING GROUP, INC.

77 North Kendall Ave. • Bradford, PA • 16701 • Phone: 814.368.1200
Fax 814.368.4563 • e-mail:arg@amref.com • www.amref.com