

KENSOL[®]

INDUSTRIAL PRODUCTS

KENSOL[®] 30

(C.A.S. 8052-41-3)

Category:	NAPHTHA				
Generic Name:	REGULAR MINERAL SPIRITS (RMS), STODDARD SOLVENT				
Description:	105°F MINIMUM FLASH POINT MINERAL SPIRITS				
Applications:	PARTS CLEANER, PAINT THINNER, CHARCOAL STARTER, USED IN HAND CLEANERS, ASPHALT CUTBACKS, INDUSTRIAL CLEANERS BROAD RANGE OF USES.				
Product Code:	F10-4111				
Regulatory:	Vapor pressure meets the requirements of Pennsylvania Code 025 Section 129.63(a)4 for use as a solvent in degreasing operations in cold cleaning machines. Vapor pressure also meets the requirements of the New York Codes, Rules, and Regulations 6 NYCRR Part 226.3(a) 4 for use as a solvent in metal cleaning processes.				
ASTM METHOD	DESCRIPTION	TYPICAL VALUE	MIN	SPECIFICATION MAX	
	LB/GAL	6.43	6.40		6.47
D-4052	GRAVITY, API	51.4	50.4		52.3
D-56	FLASH POINT, °F (TCC)		105		
D-611	ANILINE POINT, °C	65			
D-1133	KAURI BUTANOL VALUE	32.52			
D-5949	POUR POINT, °C	-60			
D-2622	SULFUR, WT %	< 0.0005			0.0050
D-156	COLOR, SAYBOLT	+30			
D-86	DISTILLATION, °F				
	IBP	310			
	5%	322	310		
	50%	341			
	95%	375			
	EBP	393			410
D-2879	VAPOR PRESSURE, MM Hg @ 68°F	0.62			
D-1319	FLUOR. INDICATOR ANALYSIS				
	AROMATICS, VOL %	10.5			
	OLEFINS, VOL %	0.4			
	SATURATES, VOL %	89.1			
OLFACTORY	ODOR	MILD PETROLEUM SOLVENT			
					Rev. 5/19/11

THE CHEMICAL, PHYSICAL, AND PHYSIOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN FULLY INVESTIGATED AND ITS HANDLING, MIXING WITH INCOMPATIBLE CHEMICALS OR USE MAY BE HAZARDOUS. THIS PRODUCT IS FOR INDUSTRIAL USE ONLY. DO NOT INGEST. KEEP AWAY FROM CHILDREN. MATERIAL SAFETY DATA SHEETS ARE AVAILABLE ON REQUEST.

NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING PATENT WARRANTIES, OR WARRANTIES OF MERCHANTABILITY OF FITNESS FOR USE, ARE MADE BY AMERICAN REFINING GROUP, INCORPORATED WITH RESPECT TO PRODUCTS DESCRIBED OR INFORMATION SET FORTH HEREIN, NOTHING CONTAINED HEREIN SHALL CONSTITUTE A PERMISSION OR RECOMMENDATION TO PRACTICE ANY INVENTION COVERED BY A PATENT WITHOUT A LICENSE FROM THE OWNER OF THE PATENT.

