

KENSOL®

INDUSTRIAL PRODUCTS

KENSOL® 48H

(C.A.S. 64742-47-8)

Category:	KENSOL HYDROTREATED DISTILLATE			
Generic Name:	ALUMINUM ROLLING OIL/INK OIL			
Description:	HYDROTREATED MIDDLE DISTILLATE			
Product Code:	H10-4115			
Regulatory:	21 CFR 178.3910 - surface lubricants used to manufacture metallic articles that contact food (FDA regulations).			

ASTM METHOD	DESCRIPTION	TYPICAL VALUE	SPECIFICATION		
			MIN		MAX
	LB/GAL	6.58			
D-4052	GRAVITY, API	47.4	46.8		48.0
D-5949	POUR POINT, °C	-39			
D-92	FLASH POINT, COC, °F	185			
D-56	FLASH POINT, TCC, °F		160		
D-2161	VISCOSITY @ 100°F, SUS	31.2			
D-445	VISCOSITY @ 40°C, cSt	1.56			
D-7039	SULFUR, ppm				10
D-1319	FIA ANALYSIS, Vol%				
	AROMATICS	11.5			
	OLEFINS	0.5			
	SATURATES	88			
D-86	DISTILLATION, °F				
	IBP	391	380		
	10%	409			
	50%	422			
	90%	443			
	EBP	465			475
D-1133	KAURI BUTANOL VALUE	28.6			
D-611	ANILINE POINT, °C	74.4			
D-156	COLOR, SAYBOLT	+30	+28		
D-6304	KF MOISTURE, ppm				100
	ODOR	Mild Distillate			
					Rev.4/27/10

THE CHEMICAL, PHYSICAL, AND PHYSIOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN FULLY INVESTIGATED AND ITS HANDLING, MIXING WITH INCOMPATIBLE CHEMICALS OR USE MAY BE HAZARDOUS. THIS PRODUCT IS FOR INDUSTRIAL USE ONLY. DO NOT INGEST. KEEP AWAY FROM CHILDREN. MATERIAL SAFETY DATA SHEETS ARE AVAILABLE ON REQUEST.

NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING PATENT WARRANTIES, OR WARRANTIES OF MERCHANTABILITY OF FITNESS FOR USE, ARE MADE BY AMERICAN REFINING GROUP, INCORPORATED WITH RESPECT TO PRODUCTS DESCRIBED OR INFORMATION SET FORTH HEREIN, NOTHING CONTAINED HEREIN SHALL CONSTITUTE A PERMISSION OR RECOMMENDATION TO PRACTICE ANY INVENTION COVERED BY A PATENT WITHOUT A LICENSE FROM THE OWNER OF THE PATENT.

