

# KENSOL<sup>®</sup>

## INDUSTRIAL PRODUCTS

### KENSOL<sup>®</sup> 61H

(C.A.S. 64742-46-7)

[REACH Registration # 01-2119489867-12-0013]

<b>Category:</b>	KENSOL HYDROTREATED DISTILLATE
<b>Generic Name:</b>	HYDROTREATED 40 NEUTRAL/MINERAL SEAL OIL (MSO)
<b>Description:</b>	HYDROTREATED MIDDLE DISTILLATE
<b>Product Code:</b>	H10-4129
<b>Regulatory:</b>	21 CFR 178.3620© - mineral oil as components of non-food articles intended for use in contact with food (FDA regulations).

ASTM METHOD	DESCRIPTION	TYPICAL VALUE	SPECIFICATION	
			MIN	MAX
	LB/GAL	6.87		
D-4052	GRAVITY, API		39	41
D-5949	POUR POINT, °C	-9		
D-92	FLASH POINT, °F	285	275	
D-2161	VISCOSITY @ 100°F, SUS	40.9		
D-445	VISCOSITY @ 40°C, cSt		3.9	4.5
D-7039	SULFUR, ppm			50
D-156	COLOR, SAYBOLT	+28	+26	
D-2549	AROMATICS, Mass%	10		
	NON-AROMATICS, Mass%	90		
	ODOR	Light		
	VISUAL	Clear&Bright		
D-86	DISTILLATION, °F			
	IBP	530	520	
	5%	546		
	50%	572		
	95%	615		
	EBP	623		625
D-1133	KAURI BUTANOL VALUE	22.5		
D-611	ANILINE POINT, °C	88.3		
D-6304	KF MOISTURE, ppm			100
				Rev. 2/9/11

THE CHEMICAL, PHYSICAL, AND PHYSIOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN FULLY INVESTIGATED AND ITS HANDLING, MIXING WITH INCOMPATIBLE CHEMICALS OR USE MAY BE HAZARDOUS. THIS PRODUCT IS FOR INDUSTRIAL USE ONLY. DO NOT INGEST. KEEP AWAY FROM CHILDREN. MATERIAL SAFETY DATA SHEETS ARE AVAILABLE ON REQUEST.

NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING PATENT WARRANTIES, OR WARRANTIES OF MERCHANTABILITY OF FITNESS FOR USE, ARE MADE BY AMERICAN REFINING GROUP, INCORPORATED WITH RESPECT TO PRODUCTS DESCRIBED OR INFORMATION SET FORTH HEREIN, NOTHING CONTAINED HEREIN SHALL CONSTITUTE A PERMISSION OR RECOMMENDATION TO PRACTICE ANY INVENTION COVERED BY A PATENT WITHOUT A LICENSE FROM THE OWNER OF THE PATENT.

