

# KENDEX<sup>®</sup>

## INDUSTRIAL PRODUCTS

### KENDEX<sup>®</sup> MNE

(C.A.S. 64742-04-7)

**Category:** CUSTOM BLEND

**Generic Name:** MEDIUM NEUTRAL EXTRACT

**Description:** REJUVENATION COMPOUND, EXTRACT

**Product Code:** J10-4577

**Applications:** ASPHALT AND RUBBER APPLICATIONS

ASTM METHOD	DESCRIPTION	TYPICAL VALUE	SPECIFICATION		
			MIN		MAX
	LB/GAL	8.01			
	SPECIFIC GRAVITY	0.961			
D-1298A	GRAVITY, API	15.0			
D-445	VISCOSITY @ 40°C, cSt	92.20			
D-445	VISCOSITY @ 100°C, cSt	7.40			
D-2161	VISCOSITY @ 212°F, SUS	35.00			
D-2270	VISCOSITY INDEX	-17			
D-5949	POUR POINT, °C	-24			
D-92	FLASH POINT, COC, °F/°C	420 / 216			
	MOLECULAR WEIGHT	349			
D-1218	REFRACTIVE INDEX, 20°C	1.5218			
	% C IN AROMATICS	30.25			
	% C IN NAPHTHENICS	14.43			
	% C IN PARAFFINICS	55.33			
	AROMATICS				
	MONONUCLEAR, %	0.490			
	DINUCLEAR, %	6.445			
	POLYNUCLEAR, %	13.800			
	SATURATES, %	49.830			
D-86	BOILING BELOW 700°F, %	13			
D-6304	KF MOISTURE, ppm				400
					Rev. 1/18/10

THE CHEMICAL, PHYSICAL, AND PHYSIOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN FULLY INVESTIGATED AND ITS HANDLING, MIXING WITH INCOMPATIBLE CHEMICALS OR USE MAY BE HAZARDOUS. THIS PRODUCT IS FOR INDUSTRIAL USE ONLY. DO NOT INGEST. KEEP AWAY FROM CHILDREN. MATERIAL SAFETY DATA SHEETS ARE AVAILABLE UPON REQUEST.

NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING PATENT WARRANTIES, OR WARRANTIES OF MERCHANTABILITY OF FITNESS FOR USE, ARE MADE BY AMERICAN REFINING GROUP, INCORPORATED WITH RESPECT TO PRODUCTS DESCRIBED OR INFORMATION SET FORTH HEREIN, NOTHING CONTAINED HEREIN SHALL CONSTITUTE A PERMISSION OR RECOMMENDATION TO PRACTICE ANY INVENTION COVERED BY A PATENT WITHOUT A LICENSE FROM THE OWNER OF THE PATENT.

