KENDEX®

INDUSTRIAL PRODUCTS

KENDEX® 0834

C.A.S. 8052-42-4

[REACH Registration # 01-2119480172-44-0055]

Category:	RESINS
Generic Name:	HEAVY RESINS / 2600 VISCOSITY RESIN
Description:	HEAVY VISCOSITY, BLACK, TACKY, PENN-GRADE RESINS. MAY REQUIRE HEAT TO REMOVE FROM SHIPPING CONTAINER.
Product Code:	L10-4554
Applications:	USED AS A VISCOSITY BUILDER FOR METALWORKING FLUIDS AND STRAIGHT OILS. USED IN QUENCH OILS TO CONTROL QUENCHING RATE.

ASTM METHOD	DESCRIPTION	TYPICAL VALUE	SPECIFICATION MIN		MAX
	LB/GAL	7.95			
D-1298A	GRAVITY, API	16.8			
D-445	VISCOSITY @ 40ºC, cSt	48,000			
D-445	VISCOSITY @ 100ºC, cSt	540	450		575
D-445	VISCOSITY @ 210ºF, SUS	2600			
D-2270	VISCOSITY INDEX	100			
D-92	FLASH POINT, ºF (COC)	650	625		
D-5949	POUR POINT, ºC	27			
D-1500	COLOR, ASTM	OPAQUE			
D-524	RAMSBOTTOM CARBON RESIDUE,	9.75			
D-6304	KARL FISHER MOISTURE, PPM				100
D-6560/IP 143	ASPHALTENES CONTENT	<1.0% wt			
	METHOD IP 346	<3.0% m/m PCA Extract			

Rev. 2/9/11

THE CHEMICAL, PHYSICAL, AND PHYSIOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN FULLY INVESTIGATED AND ITS HANDLING, MIXING WITH INCOMPATIBLE CHEMICALS OR USE MAY BE HAZARDOUS. THIS PRODUCT IS FOR INDUSTRIAL USE ONLY. DO NOT INGEST. KEEP AWAY FROM CHILDREN. MATERIAL SAFETY DATA SHEETS ARE AVAILABLE UPON REQUEST.

NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING PATENT WARRANTIES, OR WARRANTIES OF MERCHANTABILITY OF FITNESS FOR USE, ARE MADE BY AMERICAN REFINING GROUP, INCORPORATED WITH RESPECT TO PRODUCTS DESCRIBED OR INFORMATION SET FORTH HEREIN, NOTHING CONTAINED HEREIN SHALL CONSTITUTE A PERMISSION OR RECOMMENDATION TO PRACTICE ANY INVENTION COVERED BY A PATENT WITHOUT A LICENSE FROM THE OWNER OF THE PATENT.

AMERICAN REFINING GROUP, INC.

ARB102 (5/02)

77 North Kendall Avenue • Bradford, Pennsylvania • 16701 • Phone: 814.368.1200

Fax 814.368.4563 • e-mail:arg@amref.com • www.amref.com • ISO 9001:2008