KENDEX®

INDUSTRIAL PRODUCTS

KENDEX® 0898

C.A.S. 64742-16-1

Category: RESINS

Generic Name: INTERMEDIATE RESINS

Description: INTERMEDIATE VISCOSITY, BLACK, STICKY, PENN-GRADE RESINS

Product Code: L10-4618

Applications: VISCOSITY BUILDER FOR METALWORKING APPLICATIONS

ASTM METHOD	DESCRIPTION	TYPICAL VALUE	SPECIFICATION		
			MIN		MAX
	LB/GAL	7.74			
D-1298A	GRAVITY, API	20.7			
D-445	VISCOSITY @ 40ºC, cSt	3304			
D-2161	VISCOSITY @ 100ºC, cSt		105.6		123.6
D-2270	VISCOSITY INDEX	95.0			
D-92	FLASH POINT, COC, ºF (ºC)	630 (332)	600 (316)		
D-5949	POUR POINT, ºC	3			
D-1500	COLOR, ASTM	OPAQUE			
D-524	RAMSBOTTOM CARBON RESIDUE,%	3.25			
D-6304	KARL FISHER MOISTURE, ppm				100

Rev. 1/18/10

THE CHEMICAL, PHYSICAL, AND PHYSIOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN FULLY INVESTIGATED AND ITS HANDLING, MIXING WITH INCOMPATIBLE CHEMICALS OR USE MAY BE HAZARDOUS. THIS PRODUCT IS FOR INDUSTRIAL USE ONLY. DO NOT INGEST. KEEP AWAY FROM CHILDREN. MATERIAL SAFETY DATA SHEETS ARE AVAILABLE UPON REQUEST.

NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING PATENT WARRANTIES, OR WARRANTIES OF MERCHANTABILITY OF FITNESS FOR USE, ARE MADE BY AMERICAN REFINING GROUP, INCORPORATED WITH RESPECT TO PRODUCTS DESCRIBED OR INFORMATION SET FORTH HEREIN, NOTHING CONTAINED HEREIN SHALL CONSTITUTE A PERMISSION OR RECOMMENDATION TO PRACTICE ANY INVENTION COVERED BY A PATENT WITHOUT A LICENSE FROM THE OWNER OF THE PATENT.

AMERICAN REFINING GROUP, INC.

ARB102 (5/02)

77 North Kendall Avenue • Bradford, Pennsylvania • 16701 • Phone: 814.368.1200
Fax 814.368.4563 • e-mail:arg@amref.com • www.amref.com • ISO 9001:2008