

A M E R I C A N R E F I N I N G G R O U P I N C .
M A T E R I A L S A F E T Y D A T A S H E E T

LOW POUR 2 STROKE ENGINE OIL - RED ASHLESS (TC-W3)

PRODUCT CODE: M30-7240

NFPA HAZARD RATING

4 – Extreme
3 – High
2 – Moderate
1 – Insignificant

PRODUCT NFPA HAZARD RATING

Health – 1
Fire – 2
Reactivity - 0

PAGE 1

DIVISION AND LOCATION---SECTION I

Division: LUBRICANTS AND SPECIALTY PRODUCTS DIVISION

Location: BRADFORD, PENNSYLVANIA

77 N. KENDALL AVE, BRADFORD, PA, 16701

Emergency Telephone Number: (814) 368-1297

Transportation Emergency: CHEMTREC 1-(800) 424-9300 (U.S. and Canada)

CHEMICAL AND PHYSICAL PROPERTIES---SECTION II

Chemical Name:

petroleum hydrocarbon plus additives

Formula: not applicable

Hazardous Decomposition Products:

carbon monoxide and carbon dioxide from burning.

oxides of nitrogen

Incompatibility (Keep away from):

strong oxidizers such as hydrogen peroxide, bromine, and chromic acid.

<u>Product Components</u>	<u>CAS No.</u>	<u>% (Volume)</u>
Solvent Refined Heavy Paraffinic Distillate	64741-88-4	20-30
Hydrotreated Heavy Paraffinic Distillate	64742-54-7	15-25
Solvent Refined Residual Oil	64742-01-4	10-15
Hydrotreated Middle Distillate	64742-46-7	15-20
Stoddard Solvent	8052-41-3	5 - 10
Additives	Mixture	15 - 20

Form: liquid

Odor : solvent

Appearance: liquid

Color: red

Specific Gravity (water=1): 0.86

Boiling Point: greater than 180°C (356°F)

PourPoint: -39°C (-38°F)

Solubility in Water (by weight %): 0 at 20°C

Volatile (by weight %): 0

Evaporation Rate: (n-butyl acetate = 1) . 01

Vapor Pressure (mm Hg at 20°C): .2

Vapor Density (air=1) : not applicable

pH (as is) : not applicable

Stability: Product is stable under normal conditions

Viscosity SUS at 100°F: Greater than or = to 100

A M E R I C A N R E F I N I N G G R O U P I N C .
M A T E R I A L S A F E T Y D A T A S H E E T

LOW POUR 2 STROKE ENGINE OIL - RED ASHLESS (TC-W3)

PRODUCT CODE: M30-7240

PAGE 2

FIRE AND EXPLOSION DATA---SECTION III

Special Fire Fighting Procedures:

Do not use water except as fog.

Unusual Fire and Explosion Hazards:

Do not cut, weld, braze, solder, drill, grind or expose containers, drums, tanks, etc. of product to heat, flame, sparks, static electricity or other sources of ignition; they may ignite explosively.

Flashpoint: (Method Used) Pensky-Martens closed-cup greater than 65°C (150°F)

Flammable limits %: not applicable

Extinguishing agents:

Drychemical or Waterfog or CO₂ or Foam

Closed containers exposed to fire may be cooled with water.

HEALTH HAZARD DATA---SECTION IV

Permissible concentrations (air):

If used in applications where a mist may be generated, observe a TWA/PEL of 5 mg/m³ for mineral oil mist (OSHA and ACGIH).

Chronic effects of overexposure:

Prolonged or repeated skin contact may cause dermatitis (skin irritation)

Acute toxicological properties:

no data available

Emergency First Aid Procedures:

Eyes: Immediately flush with large quantities of water for at least 15 minutes and call a physician.

Skin Contact: Remove excess with cloth or paper. Wash thoroughly with soap and water.

Inhalation: Remove victim to fresh air. Call a physician.

If Swallowed: Call a physician immediately. DO NOT induce vomiting. (Vomiting may cause aspiration into lungs resulting in chemical pneumonia.)

ROUTES OF ENTRY:

Inhalation, skin/eye contact, ingestion

TARGET ORGAN(S):

Respiratory system, central nervous system, skin and eyes

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Preexisting eye, skin and respiratory disorders.

(Continued on next page)

A M E R I C A N R E F I N I N G G R O U P I N C .
M A T E R I A L S A F E T Y D A T A S H E E T

LOW POUR 2 STROKE ENGINE OIL - RED ASHLESS (TC-W3)

PRODUCT CODE: M30-7240

PAGE 3

SPECIAL PROTECTION INFORMATION---SECTION V

Ventilation Type Required (Local,mechanical,special):

Local if necessary to maintain allowable PEL(permissible exposure limit) or TLV(threshold limit value)

Respiratory Protection (Specify type):

Use NIOSH/MSHA certified respirator with dual organic vapor/mist and particulates cartridge if vapor concentration exceeds permissible exposure limit.

Protective Gloves:

neoprene type

Eve Protection:

chemical safety goggles

Other Protective Equipment:

none

HANDLING OF SPILLS OR LEAKS---SECTION VI

Procedures for Clean-Up:

Avoid all ignition sources such as flames and sparks. Insure good ventilation.

If volume is significant, transfer into containers for disposal. Seal containers tightly. Absorb on an inert ingredient such as earth, sand or vermiculite. Sweep up and dispose of according to Federal, State and local regulations.

Waste Disposal:

Dispose of in accordance with all applicable federal, state and local regulations.

SPECIAL PRECAUTIONS---SECTION VII

Precautions to be taken in handling and storage:

Do not handle or store at temperatures over

Maximum Storage Temperature : 60°C (140°F)

TRANSPORTATION DATA---SECTION VIII

D.O.T. : Regulated

U.S. D.O.T. Proper Shipping Name: Combustible Liquid NOS

U.S. D.O.T. Hazard Class: Combustible Liquid, 3

I.D. Number: NA 1993, PGIII, (Contains Mineral Spirits), ERG 128

Reportable Quantity: not applicable

Freight Classification: Petroleum Lubricating Oil

Special Transportation Notes:

DOMESTIC: Unregulated by DOT when shipped in containers of less than 118.9 gallons.

(Continued on next page)

A M E R I C A N R E F I N I N G G R O U P I N C .
M A T E R I A L S A F E T Y D A T A S H E E T

LOW POUR 2 STROKE ENGINE OIL - RED ASHLESS (TC-W3)

PRODUCT CODE: M30-7240

PAGE 4

COMMENTS

The additive mixtures in this product have been declared a trade secret by the additive manufacturers.

Prepared by: Monica C Mathers

Title: Product Compliance Coordinator

Original Date: 03/23/99

Revision Date: 05/15/08

Supersedes_: 01/16/06

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.