

A M E R I C A N R E F I N I N G G R O U P I N C .
M A T E R I A L S A F E T Y D A T A S H E E T

STATIONARY GAS ENGINE OIL SAE 15W-40 LOW ASH

PRODUCT CODE: M31-7256

NFPA HAZARD RATING

4 – Extreme
3 – High
2 – Moderate
1 – Insignificant

PRODUCT NFPA HAZARD RATING

Health – 0
Fire – 1
Reactivity - 0

PAGE 1

DIVISION AND LOCATION---SECTION I

Division: LUBRICANTS AND SPECIALTY PRODUCTS DIVISION

Location: BRADFORD, PENNSYLVANIA

77 N. KENDALL AVE, BRADFORD, PA, 16701

Emergency Telephone Number: (814) 368-1297

Transportation Emergency: CHEMTREC 1-(800) 424-9300 (U.S. and Canada)

CHEMICAL AND PHYSICAL PROPERTIES---SECTION II

Chemical Name:

petroleum hydrocarbon plus additives

Formula: not applicable

Hazardous Decomposition Products:

carbon monoxide and carbon dioxide from burning.
oxides of phosphorous from burning
oxides of sulfur

Incompatibility (Keep away from):

strong oxidizers such as hydrogen peroxide, bromine, and chromic acid.

<u>Product Components</u>	<u>CAS No.</u>	<u>% (Volume)</u>
Hydrotreated Heavy Paraffinic Distillate	64742-54-7	80-90
Additives	Mixture	10-20

Form: liquid

Odor : motor oil

Appearance: liquid

Color: dark brown

Specific Gravity (water=1): 0.88

Boiling Point: greater than 330°C (625°F)

Pour Point: less than -30°C (-22°F)

Solubility in Water (by weight %): 0 at 20°C

Volatile (by weight %): 0

Evaporation Rate: 0

Vapor Pressure (mm Hg at 20°C): 0

Vapor Density (air=1) : not volatile

pH (as is) : not applicable

Stability: Product is stable under normal conditions

Viscosity SUS at 100°F: Greater than or = to 100

(Continued on next page)

A M E R I C A N R E F I N I N G G R O U P I N C .
M A T E R I A L S A F E T Y D A T A S H E E T

STATIONARY GAS ENGINE OIL SAE 15W-40 LOW ASH

PRODUCT CODE: M31-7256
PAGE 2

FIRE AND EXPLOSION DATA---SECTION III

Special Fire Fighting Procedures:

Do not use water except as fog.

Unusual Fire and Explosion Hazards:

Do not cut, weld, braze, solder, drill, grind or expose containers, drums, tanks, etc. of product to heat, flame, sparks, static electricity or other sources of ignition; they may ignite explosively.

Flashpoint: (Method Used) Cleveland open cup greater than 205°C (400°F)

Flammable limits % : not applicable

Extinguishing agents:

Drychemical or Waterfog or CO₂ or Foam

Closed containers exposed to fire may be cooled with water.

HEALTH HAZARD DATA---SECTION IV

Permissible concentrations (air):

If used in applications where a mist may be generated, observe a TWA/PEL of 5 mg/m³ for mineral oil mist (OSHA and ACGIH).

Chronic effects of overexposure:

Prolonged or repeated skin contact may cause dermatitis (skin irritation)

Acute toxicological properties:

no data available

Emergency First Aid Procedures:

Eyes: Immediately flush with large quantities of water for at least 15 minutes and call a physician.

Skin Contact: Remove excess with cloth or paper. Wash thoroughly with soap and water.

Inhalation: Remove victim to fresh air. Call a physician.

If Swallowed: Contact a physician immediately.

SPECIAL PROTECTION INFORMATION---SECTION V

Ventilation Type Required (Local, mechanical, special):

Local if necessary to maintain allowable PEL(permissible exposure limit) or TLV(threshold limit value)

Respiratory Protection (Specify type):

Use NIOSH/MSHA certified respirator with dual organic vapor/mist and particulates cartridge if vapor concentration exceeds permissible exposure limit.

Protective Gloves:

neoprene type

Eye Protection:

chemical safety goggles

(Continued on next page)

A M E R I C A N R E F I N I N G G R O U P I N C .
M A T E R I A L S A F E T Y D A T A S H E E T

STATIONARY GAS ENGINE OIL SAE 15W-40 LOW ASH

PRODUCT CODE: M31-7256
PAGE 3

(Section V continued)

Other Protective Equipment:
none

HANDLING OF SPILLS OR LEAKS---SECTION VI

Procedures for Clean-Up:

Transfer bulk of mixture into another container. Absorb residue with an inert material such as earth, sand, or vermiculite. Sweep up and dispose as solid waste in accordance with local, state, and federal regulations.

Waste Disposal:

Dispose of in accordance with all applicable federal, state and local regulations.

SPECIAL PRECAUTIONS---SECTION VII

Precautions to be taken in handling and storage:

Do not handle or store at temperatures over

Maximum Storage Temperature: 60°C (140°F)

TRANSPORTATION DATA---SECTION VIII

D.O.T.: Not Regulated

Reportable Quantity: not applicable

Freight Classification: Petroleum Lubricating Oil

Special Transportation Notes:

none

ENVIRONMENTAL/SAFETY REGULATIONS---SECTION IX

Section 313 (Title III Superfund Amendment and Reauthorization Act):

This product does not contain any chemical in sufficient quantity to be subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

COMMENTS

The additive mixtures in this product have been declared a trade secret by the additive manufacturers.

(Continued on next page)

A M E R I C A N R E F I N I N G G R O U P I N C .
M A T E R I A L S A F E T Y D A T A S H E E T

STATIONARY GAS ENGINE OIL SAE 15W-40 LOW ASH

PRODUCT CODE: M31-7256
PAGE 4

(COMMENTS continued)

Prepared by: Monica C Mathers

Title: Product Compliance Coordinator

Original Date: 09/17/97

Revision Date: 06/05/08

Supersedes: 11/08/06

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.