



PRIVATE LABEL & GENERIC LUBRICANTS

SPECIFICATION SHEET

PRODUCT: **PASSENGER CAR MOTOR OIL SAE 10W-40
(SF / CC-CD)**

PRODUCT CODE: **M03-7920**

PERFORMANCE CATEGORY: **Meets API SERVICE SF / CC-CD**

ASTM METHOD	SPECIFICATION	MINIMUM	MAXIMUM	TYPICAL
D-4052	GRAVITY, API LB/GAL			30.8 7.274
D-445	VISCOSITY @ 40 °C, cSt			102.35
D-445	VISCOSITY @ 100 °C, cSt			14.7
D-2270	VISCOSITY INDEX			158
D-1500	COLOR			3
D-5949	POUR POINT °C (Max.)			-33
D-92	FLASH POINT °F			
D-5293	CCS @ -25° C, cP (Max.)			7000
D-4684	MRV @ -30° C < 35 Pa, cP			41400
D-2896	TBN			6.2
D-874	SULFATED ASH, Mass %			0.8
D-6304	KF MOISTURE, ppm			
D-6481	ZINC, Mass %			0.088
D-6481	CALCIUM, Mass %			0.202
D-4294	SULFUR			0.34
	PHOSPHORUS			0.08