



PRIVATE LABEL & GENERIC LUBRICANTS

SPECIFICATION SHEET

PRODUCT: **PASSENGER CAR MOTOR OIL, SAE 10W-40**

PRODUCT CODE: **M03-7920**

PERFORMANCE CATEGORY: **API SERVICE SF/CC-CD**

ASTM METHOD	SPECIFICATION	MINIMUM	MAXIMUM	TYPICAL
D-1298A	GRAVITY, API			30.8
	LB/GAL			7.274
D-445	VISCOSITY @ 40 °C, cSt			102.35
D-445	VISCOSITY @ 100 °C, cSt	14.0	15.5	14.7
D-2270	VISCOSITY INDEX			158
D-1500	COLOR			3
D-5949	POUR POINT °C		-33	
D-92	FLASH POINT °F			
D-5293	CCS @ -25° C, cP		7000	
D-4684	MRV @ -30° C < 35 Pa, cP			41400
D-2896	TBN			6.2
D-874	SULFATED ASH, Mass %			0.8
D-6304	KF MOISTURE, ppm			
D-6481	ZINC, Mass %	0.079	0.097	0.088
D-6481	CALCIUM, Mass %	0.182	0.221	0.202
D-4294	SULFUR			0.34
	PHOSPHORUS			0.08