

Safety Data Sheet

Prepared according to GHS

1. Identification

Product Name Kensol® 61H

Product Code 4129

Recommended Use Mineral Seal Oil

Company
American Refining Group, Inc.
77 North Kendall Avenue

Bradford, PA 16701 www.amref.com msds@amref.com

Emergency Telephone Chemtrec 1-800-424-9300 (24 HRS)

Number(s) ARG: 814-368-1297 (24 HRS)

2. Hazards Identification

GHS Classification Aspiration Hazard Category 1

Signal Word DANGER!

Hazard Statements May be fatal if swallowed and enters airways.



Precautionary Statements

GHS Pictogram

If swallowed: immediately call a poison center/ doctor to specify the appropriate source of emergency medical advice.

Do NOT induce vomiting.

3. Composition / Information on Ingredients

CAS No.	Component	Common Name	Percent
64742-46-7	Hydrotreated distillate, middle	Mineral Seal Oil	100%

4. First Aid Measures

Eyes Check for and remove any contact lenses. Immediately flush eyes

with plenty of water for at least 15 minutes, occasionally lifting the

upper and lower eyelids. Get medical attention immediately.

Skin

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

Wash clothing before reuse. Clean shoes thoroughly before reuse.

Kensol® 61H	Revision Date: 10/10/2016	American Refining Group, Inc.
4129	Revision #:5	Page 2 of 7
	4. First Aid Measures	

Get medical attention immediately.

InhalationProduct is not expected to present any inhalation hazard at ambient conditions. If aerosolization and/or misting occurs and a person is over-exposed, move exposed person to fresh air. If not breathing, if

over-exposed, move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention

immediately.

Ingestion DO NOT INDUCE VOMITING. If conscious, rinse out mouth with

water. Seek medical attention immediately.

Symptoms(**Acute and delayed**) May be fatal if swallowed and enters airways.

Note to Physicians

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been

treatment specialist immediately if large quantities have been

ingested or inhaled.

5. Fire Fighting Measures

Suitable Extinguishing Media

Use dry chemical, CO₂, water spray (FOG) or foam

Unsuitable Extinguishing Media

Avoid solid water stream as it may scatter and spread fire.

Specific Hazards Arising from Chemical

Elevated temperatures can lead to the formation of irritating fumes and vapors. Decomposing products may include the following materials: Carbon dioxide and Carbon monoxide.

Protective Equipment and Precautions for Firefighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental Release Measures

Personal Precautions

Put on appropriate personal protective equipment.

Environmental Precautions

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas.

Methods for Containment

Stop leak if without risk.

Methods for Cleanup

Cover liquid spill with sand, earth or other noncombustible absorbent material. Cover powder spill with plastic sheet or tarp to minimize spreading. Pick up and transfer to properly labeled container

7. Handling and Storage

Handling Procedures

Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Use non-sparking tools.

Shipping and Storing Procedures

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat. Protect from light. Keep in properly labeled containers. Keep out of the reach of children.

7. Handling and Storage

Incompatibilities:

Oxidizing Agents

8. Exposure Controls / Personal Protection

Component Exposure Limits

Oil Mist (mineral)

ACGIH TLV: TWA: 5 mg/m^3 10 mg/m^3 N/A ppm TWA: STEL: N/A ppm STEL: 5 mg/m^3 N/A mg/m³ N/A ppm **OSHA PEL:** TWA: N/A ppm **TWA** STEL: STEL: 10 mg/m^3 5 mg/m^3 **NIOSH REL:** TWA: N/A ppm **TWA** STEL: N/A ppm STEL:

N/A signifies not available

Engineering ControlsMaterial should be handled in enclosed vessels and equipment. Use

only in adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

airborne contaminants below any recommended or statutory limits.

Eye/Face Protection Chemical goggles or face shield.

Skin Protection Chemical resistant, impervious gloves complying with an approved

standard should be worn at all times. Coveralls, apron, and boots as

necessary to minimize contact.

Respiratory Protection Respirator may only be needed if product is aerosolized and/or misted.

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicated this is necessary. Respirator selection must be based on known or anticipated exposure

levels.

General Hygiene Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove

potentially contaminated clothing.

9. Physical and Chemical Properties

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Please see the Product Specification Sheet for further information.

Appearance	Clear and bright	Flammability	Not Available
Physical State	Liquid	Upper/Lower	Not Available
		Flammability Limits	
Odor	Petroleum Oil	Vapor Pressure(20℃	0.00
		mm Hg)	
Odor Threshold	Not Available	Vapor Density	Not Available
pH	Not Available	Relative Density (lbs/gal)	6.8
Melting/Freezing Point	Not Available	Water Soluble	No
(°F)			
Initial Boiling Point (F)	530	Partition Coefficient: n-	3.3 to >6
		octanol/water	
Boiling Range (%)	530-623	Auto-ignition	Not Available
		Temperature (°F)	
Flash Point (°F)	285	Decomposition	Not Available
Cleveland Open Cup ASTM D-92		Temperature (°F)	

Kensol® 61H Revision Date: 10/10/2016 American Refining Group, Inc. 4129 Revision #:5 Page 4 of 7

9. Physical and Chemical Properties			
Evaporation Rate	Not Available	Viscosity (40 °C mm²/s)	3.9-4.5
Volatile Organic	407.3	Aromatic Content	10
Compounds (g/L)		(Typical Mass %)	

10. Chemical Stability & Reactivity Information

ReactivityPolymerization will not occurChemical StabilityStable under normal conditionsHazardous ReactionsNone, under normal processing.Conditions to AvoidHigh temperatures, flames, sparksIncompatibilityStrong acids and oxidizing materials

Hazardous Decomposition Smoke, carbon monoxide, carbon dioxide, aldehydes and other products

Products of incomplete combustion.

11. Toxicological Information

Acute Exposure

Respiratory Irritation An inhalation hazard may only arise if product is used in aerosol conditions or

if heated up. If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and upper respiratory

tract. Based on data from similar materials.

Eye Irritation May cause minimal to slight eye irritation if product is splashed in eyes and

unwashed

Skin Irritation May cause very slight transient reversible skin irritation if unwashed. May

cause slight redness and swelling.

Sensitization Not expected to cause skin or respiratory sensitization.

Aspiration Hazards If swallowed can be aspirated into lungs and cause chemical pneumonia,

varying degrees of pulmonary injury or death. If swallowed, do NOT induce

vomiting.

Chronic Exposure

Target Organ Effects No data available to indicate product or components at greater than 1% are

chronic health hazards.

Carcinogenicity This product contains mineral oils which are considered to be severely refined

and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP

346 test.

Mutagenicity No data available to indicate product or any components present at greater than

.1% are mutagenic or genotoxic.

Reproductive Toxicity No data available to indicate either product or components present at greater

than .1% that may cause reproductive toxicity.

Teratogenicity No data available to indicate product or any components contained at greater

than .1% may cause birth defects.

Analysis – LD50 / LC50

Inhalation LC50 Rat

4.6-7.64 mg/L (4HR) Aerosolized

Kensol® 61H 4129 Revision Date: 10/10/2016
Revision #:5

American Refining Group, Inc.
Page 5 of 7

Oral LD50 Rat Dermal LD50 Rabbit >5000 mg/kg >2000 mg/kg

12. Ecological Information

Component Analysis- Ecotoxicity - Aquatic Life

Duration/Test/Species Concentration/Conditions

96 Hr LL50; WAF >750 mg/L

Aquatic Vertebrates

7 Day EL50; WAF Not available mg/L

Daphnia magna

21 Day EL-50 Not available mg/L

Daphnia magna

*Kensol 61H is readily degradable and will not persist in the aquatic environment. It therefore is not expected to cause short-term toxicity to aquatic organisms. Since Kensol 61H has a low solubility in water, chronic aquatic toxicity is not expected.

Persistence & DegradabilityReadily degradedBioaccumulation PotentialNot AvailableSoil MobilityNot AvailableOther Adverse EffectsNot Available

13. Disposal Considerations

Disposal Instructions

The generation of waste should be avoided or minimized wherever possible. Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

14. Transportation Information

Emergency Response Guide No. 171 North American Emergency Response

Guide Book

UN Number Shipping Name (technical name) Hazard Packing Placard/

Class Group Label

U.S. DOT Not Regulated

IMDG Not Regulated

IATA Not Regulated

15. Regulatory Information

SARA Extremely Hazardous

This product does not contain greater than 1% of any "extremely hazardous substances" listed pursuant to Title III of the Superfund

Amendments and Reauthorization Act of 1986 (SARA) Section 302 or

SARA Section 313 Section 304 as identified in 40 CFR Part 355, Appendix A and B.

This product does not contain greater than 1.0% of the substances

This product does not contain greater than 1.0% of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR

15. Regulatory Information

Part 372.

SARA Section 311 & 312 Classifications

Acute Hazard Yes
Chronic Hazard No
Fire Hazard No
Reactivity Hazard No

CERCLA

This product does not contain any "hazardous substances" listed under the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

California Prop 65

This product is not routinely tested to determine chemical(s) known to the state of California to cause cancer and/or birth defects based on maximum impurity levels of components.

California Air Resource Board (CARB)

This product is considered a Low Vapor Pressure – Volatile Organic Compound (LVP-VOC) according to the CARB. This product meets one of the following requirements in order to be considered a LVP-VOC:

- (A) has a vapor pressure less than 0.1 mm Hg at 20°C, as determined by ARB Method 310; or
- (B) is a chemical "compound" with more than 12 carbon atoms, or a chemical "mixture" comprised solely of "compounds" with more than 12 carbon atoms, as verified by formulation data, and the vapor pressure and boiling point are unknown; or
- (C) is a chemical "compound" with a boiling point greater than 216°C, as determined by ARB Method 310; or
- (D) is the weight percent of a chemical "mixture" that boils above 216°C, as determined by ARB Method 310.

California Air Resource Board (CARB) Bin Number

20

Global Chemical Inventories

Inventory	
US TSCA	Present
EU	Present
Japan	Not available
Australia	Present
New Zealand	Present
Canada	Present
Switzerland	Not available
Korea	Present
Philippines	Not Available
China	Present
Taiwan NECI	Present

16. Other Information

Kensol® 61H 4129 Revision Date: 10/10/2016
Revision #:5

American Refining Group, Inc.

Page **7** of **7**

16. Other Information

US NFPA Ratings

Health	Fire	Reactivity
0	1	0

HMIS Ratings

Health	Fire	Physical Hazards
0	1	0

Revision Date 10 October 2016 **Revision Reason** Section 12

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS