



HYDROTREATED PRODUCT SUMMARY

ASTM Method	Description	Typical Values		
		Kensol 48H	Kensol 50H	Kensol 61H
	LB/GAL	6.58	6.72	6.87
	C.A.S. Number	64742-47-8	64742-46-7	64742-46-7
D4052	Gravity, API	47.4	43.6	40.3
D5949	Pour Point, °C (°F)	-39 (-38.2)	-33 (-27.4)	-9 (16)
D92	Flash Point, COC, °F (°C)	185 (85)	230 (110)	285 (141)
D56	Flash Point, TCC, °F (°C)	160 Min.		
D2161	Viscosity @ 100°F, SUS	31.2	34.3	40.9
D445	Viscosity @ 40°C, cSt	1.56	2.4	3.9-4.5
D7039	Sulfur, ppm	10 Max.	10 Max.	50 Max.
D1319	FIA Analysis, Vol%			
	Aromatics	11.5	10	
	Olefins	0.5	1	
	Saturates	88	89	
D2549	Aromatics, Mass %			10
	Non-Aromatics, Mass %			90
D86	Distillation, °F			
	IBP	391	445 Min.	530
	50%	422		572
	EBP	465	525 Max.	623
D1133	Kauri Butanol Value	28.6	24.5	22.5
D611	Aniline Point, °C	74.4	79.5	88.3
D156	Color, Saybolt	30 (≥28)	30 (≥28)	28 (≥26)
	Odor	Mild Dist.	Mild Dist.	Light
	Visual	Clear & Bright	Clear & Bright	Clear & Bright
	Product Code	H10-4115	H10-4118	H10-4129

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request.

No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions®

www.amref.com

814-368-1200

