



Grade No.2 Diesel

S-15 HO

(MAR — NOV)

(C.A.S. #: 64742-80-9)

Product Code: D10-8177

Grade No.2 Diesel S-15 HO

#2 ULSD Heating Oil Dyed Red (March – November)

ASTM Method	Description	Specification		
		Minimum	Maximum	Typical
D4052	Gravity, API	30.0		
D93	Flash, PMCC, °F	125		
D445	Viscosity @ 40°C, cSt	1.9	4.1	
D130	Copper Strip Corrosion		3.0	
D2622	Sulfur, %WT		0.0015	
D7039	Sulfur, mg/Kg		15.0	
D482	ASH, % Mass		0.01	
D524	Rams. Carbon, % Mass		0.35	
D5773	Cloud Point, °C (°F)			
	March – April 15		-9 (16)	
	April 16 - October		3 (37)	
	November		-9 (16)	
D2709	Water & Sedi, Vol. %		0.05	
D2624	Conduct., pS/m (C.U.)	25		
Method 15	Visual Inspection		Clear & Bright	
	Color (Dyed)	Red		
D86	Distillation, °F			
	90% (From D975)	540	640	

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request.

No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions®

www.amref.com

814-368-1200

