



# Safety Data Sheet

Prepared according to GHS

## 1. Identification

<b>Product Name</b>	<b>Grade No. 2 Diesel S-15 B-5</b>
<b>Product Code</b>	<b>8136</b>
<b>Recommended Use</b>	<i>Diesel Fuel</i>
<b>Company</b>	American Refining Group, Inc. 77 North Kendall Avenue Bradford, PA 16701 www.amref.com msds@amref.com
<b>Emergency Telephone Number(s)</b>	Chemtrec 1-800-424-9300 (24 HRS) ARG: 814-368-1297 (24 HRS)

## 2. Hazards Identification

<b>GHS Classification</b>	Germ Cell Mutagenicity Category 2 Carcinogenicity Category 2 Aspiration Hazard Category 1 Inhalation Hazard Category 4 Skin Corrosion/Irritation Category 2 Flammable Liquid Category 3
<b>Signal Word</b>	DANGER!
<b>Hazard Statements</b>	Suspected of causing genetic defects. Suspected of causing cancer. May be fatal if swallowed and enters airways. Harmful if inhaled. Causes skin irritation Flammable liquid and vapor
<b>Other Hazard Information</b>	Static accumulating liquid can become electrostatically charged even in bonded and grounded equipment Sparks may ignite liquid and vapor may cause flash fire. Liquid conductivity is <100 pS/m (picosiemans/meter) at 77°F
<b>GHS Pictogram</b>	



<b>Precautionary Statements</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
---------------------------------	--

**2. Hazards Identification**

Wear protective gloves/protective clothing/eye protection/face protection.  
If exposed or concerned: Get medical advice/attention.  
**Store locked up**  
Dispose of contents/container to in accordance with local/national regulations.  
If swallowed: Immediately call a poison center/doctor.  
**Do NOT induce vomiting.**  
Avoid breathing dust/fume/gas/mist/ vapors/spray.  
**Use only outdoors or in a well-ventilated area.**  
**If inhaled:** Remove person to fresh air and keep comfortable for breathing.  
**Wash thoroughly after handling.**  
If on skin: take off immediately all contaminated clothing. Wash with plenty of soap and water.  
If skin irritation occurs: get medical advice/attention.  
Take off contaminated clothing and wash before reuse.  
Keep away for heat/sparks/open flames/hot surfaces. – no smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment.  
Use explosion proof electrical/ventilating/lighting equipment.

**3. Composition / Information on Ingredients**

CAS No.	Component	Common Name	Percent
68476-34-6	Fuels, Diesel, No. 2	Petroleum Distillate	90-99%
61184-80-9	Soybean Oil, Me ester	BioDiesel	1-10%

**4. First Aid Measures**

**Eyes** Check for and remove any contact lenses. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Get medical attention if irritation occurs.

**Skin** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

**Inhalation** Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a color, tie, belt or waistband. Get medical attention immediately.

**Ingestion** DO NOT INDUCE VOMITING. If conscious, rinse out mouth with water. Seek medical attention immediately.

**Symptoms(Acute and delayed)** Exposure to high concentrations of vapors may cause irritation to the eyes, nose and throat, nausea, dizziness and loss of consciousness.

**Note to Physicians** No specific treatment. Treat symptomatically. Contact poison

#### 4. First Aid Measures

treatment specialist immediately if large quantities have been ingested or inhaled.

#### 5. Fire Fighting Measures

##### **Suitable Extinguishing Media**

Use dry chemical, CO<sub>2</sub>, water spray (FOG) or foam

##### **Unsuitable Extinguishing Media**

Avoid solid water stream as it may scatter and spread fire.

##### **Specific Hazards Arising from Chemical**

Elevated temperatures can lead to the formation of irritating fumes and vapors. Decomposing products may include the following materials: Carbon dioxide and Carbon monoxide.

This product is a static accumulating liquid. Static accumulating liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor may cause flash fire. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Restrict flow velocity to avoid build-up of static charge. Refer to NFPA 77, API 2003, and CENELEC CLC/TR 50404 for further guidance.

##### **Protective Equipment and Precautions for Firefighters**

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

#### 6. Accidental Release Measures

##### **Personal Precautions**

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

##### **Environmental Precautions**

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas.

##### **Methods for Containment**

Stop leak if without risk.

##### **Methods for Cleanup**

A vapor suppressing foam may be used to reduce vapors. Cover liquid spill with sand, earth or other noncombustible absorbent material. Cover powder spill with plastic sheet or tarp to minimize spreading. Pick up and transfer to properly labeled container

#### 7. Handling and Storage

##### **Handling Procedures**

Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Use non-sparking tools.

##### **Shipping and Storing Procedures**

Store in accordance with local regulations. Store in a segregated and approved area. Keep in the original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials. Do not store in unlabeled containers. Store and use away from heat, sparks, open flame or any other

**7. Handling and Storage**

ignition source. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers that retain product residue may be hazardous.

**Incompatibilities:**

Oxidizing Agents

**8. Exposure Controls / Personal Protection**

**Component Exposure Limits**

**Diesel Fuel, as total hydrocarbons**

<b>ACGIH TLV:</b>	TWA:	N/A ppm	TWA:	100 mg/m <sup>3</sup>	STEL:	N/A ppm	STEL:	N/A mg/m <sup>3</sup>
<b>OSHA PEL:</b>	TWA:	N/A ppm	TWA:	N/A mg/m <sup>3</sup>	STEL:	N/A ppm	STEL:	N/A mg/m <sup>3</sup>
<b>NIOSH REL:</b>	TWA:	N/A ppm	TWA:	N/A mg/m <sup>3</sup>	STEL:	N/A ppm	STEL:	N/A mg/m <sup>3</sup>

N/A signifies not available

**Engineering Controls**

This product is a static accumulating liquid. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Material should be handled in enclosed vessels and equipment. Use only in adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Eye/Face Protection**

Chemical goggles and face shield.

**Skin Protection**

Chemical resistant, impervious gloves complying with an approved standard should be worn at all times. Coveralls, apron, and boots as necessary to minimize contact.

**Respiratory Protection**

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicated this is necessary. Respirator selection must be based on known or anticipated exposure levels.

**General Hygiene**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing.

**9. Physical and Chemical Properties**

*Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Please see the Product Specification Sheet for further information.*

<b>Appearance</b>	Clear and Bright	<b>Flammability</b>	Flammable
<b>Physical State</b>	Liquid	<b>Upper/Lower Flammability Limits</b>	Not Available
<b>Odor</b>	Solvent	<b>Vapor Pressure</b>	Not Available
<b>Odor Threshold</b>	Not Available	<b>Vapor Density</b>	Not Available
<b>pH</b>	Not Available	<b>Relative Density (lbs/gal)</b>	Not available
<b>Melting/Freezing Point (°F)</b>	Not Available	<b>Water Soluble</b>	No

<b>9. Physical and Chemical Properties</b>			
<b>Initial Boiling Point (°F)</b>	Not available	<b>Partition Coefficient: n-octanol/water</b>	3.3 to 6
<b>Boiling Range (°F)</b>	Not Available	<b>Auto-ignition Temperature (°F)</b>	Not Available
<b>Flash Point (°F)</b>	125	<b>Decomposition Temperature (°F)</b>	Not Available
<b>Evaporation Rate</b>	Not Available	<b>Viscosity (40°C mm<sup>2</sup>/s)</b>	4.1

**10. Chemical Stability & Reactivity Information**

<b>Reactivity</b>	Polymerization will not occur
<b>Chemical Stability</b>	Stable under normal conditions. If heated product's static accumulation will rise and could cause flash fire.
<b>Hazardous Reactions</b>	None, under normal processing.
<b>Conditions to Avoid</b>	High temperatures, flames, sparks
<b>Incompatibility</b>	Strong acids and oxidizing materials
<b>Hazardous Decomposition Products</b>	Smoke, carbon monoxide, carbon dioxide, aldehydes and other products of incomplete combustion.

**11. Toxicological Information**

<b>Acute Exposure</b>	
<b>Respiratory Irritation</b>	An inhalation hazard may only arise if product is used in aerosol conditions or if heated up. If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and upper respiratory tract.
<b>Eye Irritation</b>	May cause eye irritation. Itchiness may occur.
<b>Skin Irritation</b>	Causes skin irritation. Itchiness and redness varies with exposure.
<b>Sensitization</b>	Not expected to cause skin or respiratory sensitization.
<b>Aspiration Hazard</b>	If swallowed can be aspirated into lungs and cause chemical pneumonia, varying degrees of pulmonary injury or death. If swallowed, do NOT induce vomiting.
<b>Chronic Exposure</b>	
<b>Target Organ Effects</b>	No data available to indicate product or components at greater than 1% are chronic health hazards.
<b>Carcinogenicity</b>	Dermal Carcinogenicity studies indicate that Gas oils and distillate fuels are potential skin carcinogens after repeated skin application but are not associated with the induction of systemic tumors. The skin carcinogenicity of the petroleum streams with high boiling ranges has been demonstrated to correlate with 3-7 ring PAC content. Diesel exhaust fumes are considered carcinogenic by IARC.
<b>Mutagenicity</b>	Based on in vitro studies, modeled mutagenic index greater than or equal to 1 with metabolic activation; predicts that the sample is mutagenic. Based on in vivo studies, the sample is considered negative for cytogenetic

effects.

**Reproductive Toxicity** No data available to indicate either product or components present at greater than .1% that may cause reproductive toxicity.

**Teratogenicity** No data available to indicate product or any components contained at greater than .1% may cause birth defects.

**Analysis – LD50 / LC50**

<b>Inhalation LC50 Rat</b>	1.78 mg/L
<b>Oral LD50 Rat</b>	>5000 mg/kg
<b>Dermal LD50 Rabbit</b>	>2000 mg/kg

**12. Ecological Information**

**Component Analysis- Ecotoxicity – Aquatic Life**

<b>Duration/Test/Species</b>	<b>Concentration/Conditions</b>
96 hr LL50 Aquatic Vertebrates	3.2-65 mg/L
96 hr EL50 <i>Raphidocelis subcapitata</i>	2.2-78 mg/L
7 Day EL50 <i>Daphnia magna</i>	2.0-210 mg/L

<b>Persistence &amp; Degradability</b>	Inherently biodegradable
<b>Bioaccumulation Potential</b>	Not Available
<b>Soil Mobility</b>	Not Available
<b>Other Adverse Effects</b>	Not Available

**13. Disposal Considerations**


**Disposal Instructions**

The generation of waste should be avoided or minimized wherever possible. Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

**14. Transportation Information**

**Emergency Response Guide No.** 128

*North American Emergency Response Guide Book*

	UN Number	Shipping Name (technical name)	Hazard Class	Packing Group	Placard
<b>U.S. DOT Bulk</b>	1993	Diesel Fuel	Combustible Liquid	III	
<b>U.S. DOT</b>		Not Regulated		Exempt from	

**14. Transportation Information**

Non-Bulk				labeling and placarding unless shipped via Air or Vessel	
IATA	1202	Diesel Fuel	3	III	
IMDG	1202	Diesel Fuel	3	III	

**15. Regulatory Information**

**SARA Extremely Hazardous Substances (Sections 302 & 304)**

This product does not contain greater than 1% of any “extremely hazardous substances” listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

**SARA Section 313**

This product does not contain greater than 1.0% of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

**SARA Section 311 & 312 Classifications**

**Acute Hazard** Yes  
**Chronic Hazard** Yes  
**Fire Hazard** No  
**Reactivity Hazard** No

**CERCLA**

This product does not contain any “hazardous substances” listed under the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

**California Prop 65**

This produces fumes when burnt suspected to contain chemicals known by the State of California to cause cancer and/or birth defects. Moreover, we do not routinely analyze its products for impurities which may be such chemicals.

**Global Chemical Inventories**

Inventory	
US TSCA	Present
EU	Present
Japan	Not available

Australia	Present
New Zealand	Present
Canada	Present
Switzerland	Not available
Korea	Present
Philippines	Present
China	Present
Taiwan	Present

**16. Other Information**

**US NFPA Ratings**

<b>Health</b>	<b>Fire</b>	<b>Reactivity</b>
2	2	0

**HMIS Ratings**

<b>Health</b>	<b>Fire</b>	<b>Physical Hazards</b>
2	2	0

**Revision Date** 14 July 2015  
**Revision Reason** New SDS

*The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.*

**End of SDS**