

Kensol[®] 50H

(C.A.S. #: 64742-46-7) Product Code: H10-4118

Regulatory: 21 CFR 178.3620(c) – mineral oil as components of non-food articles that contact food

[REACH Registered]

Kensol[®] 50H

Hydrotreated Distillate.

Applications: Aluminum Rolling Oil, Ink Oil, Drilling Fluids.

ASTM Method	Description	Specification		
		Minimum	Maximum	Typical
	LB/GAL			6.72
D4052	Gravity, API	43.0	44.5	43.6
D445	Viscosity @ 40°C, cSt			2.4
D2161	Viscosity @ 100°F, SUS			34.3
D92	Flash Point, °F (°C)			230 (110)
D611	Aniline Point, °C			79.5
D1319	FIA Analysis, Vol%			
	Aromatics			10
	Olefins			1
	Saturates			89
D1133	Kauri Butanol Value			24.5
D97	Pour Point, °C (°F)			-33 (-27.4)
D156	Color, Saybolt	+28		+30
D86	Distillation, °F			
	IBP	445		465
	EBP		525	519
D130	Copper Strip Corrosion			1A
D-7039	Sulfur		10	6
Olfactory	Odor			Mild Solvent

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request.

No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions[®]

www.amref.com

814-368-1200

