

Kendex® 0847

(C.A.S. #: 64742-01-4)

[REACH Registered]

Product Code: R10-4318

Kendex® 0847

Base Oil (Group I), Bright Stock, Finished Bright Stock

Applications: High Viscosity Base Oil Used in Formulating Lubricants

ASTM Method	Description	Specification		
		Minimum	Maximum	Typical
	LB/GAL			7.49
D4052	Gravity, API			26.2
D445	Viscosity @ 40°C, cSt			485
D445	Viscosity @ 100°C, cSt	30.0	33.70	32.0
D445	Viscosity @ 100°F, SUS			2600
D445	Viscosity @ 210°F, SUS			155
D2270	Viscosity Index	95.0		97.0
D92	Flash Point, °F (°C)	550 (288)		560 (293)
D5949	Pour Point, °C (°F)		-6 (21.2)	-12 (10.4)
D1500	Color ASTM			7.5
D189	Conradson Carbon Residue, %			0.85
D611	Aniline Point, °F/°C			260 (127)
D664	Neutralization Number			0.05
D3238	NDM, Aromatic Carbon, %			8
	Naphthenic Carbon, %			24
	Paraffinic Carbon, %			68

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request.

No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent



Specialty Refining Solutions®

www.amref.com

814-368-1200

