

Kendex® 165 HTLV

(C.A.S. #: 64742-65-0)

[REACH Registered]

Product Code: R11-4325

Kendex® 165 HTLV

Base Oil (Group II), Hydrotreated 165 SUS Neutral, Hydrotreated 165 SUS Low Volatility Neutral

Applications: High Viscosity Index Base Oil Used in Formulating Lubricants

	Description	Specification		
		Minimum	Maximum	Typical
	LB/GAL			7.18
D4052	Gravity, API			32.8
D445	Viscosity @ 40°C, cSt	28.0	32.0	
D445	Viscosity @ 100°C, cSt	5.2	5.6	
D2270	Viscosity Index	100		
D92	Flash Point, °F (°C)	400 (204)		
D5949	Pour Point, °C (°F)		-12 (10.4)	
D1500	Color, ASTM		0.5	L0.5
D2887	% Boiling Less Than 700°F			7.0
	50% Spec, °F			805
D2007	Saturates, %	90		
D93	Flash Point PM, °F	350		
D5800	Noack Volatility, %		15	
D7039	Sulfur, mg/kg		25	

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request.

No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions®

www.amref.com

814-368-1200

