

Kendex® 0060H

(CAS Number 64742-56-9)
Product Code: R10-4327

Regulatory: Meets 21 CFR 178.3620© mineral oil as component of non-food articles intended for use in contact with food (FDA regulations).

Kendex® 0060H

Hydrotreated Base Oil (Group I), Hydrotreated 60 SUS Neutral, Hydrotreated Light Lubricant Neutral (HLLN)

Applications: Lubricant Formulations, Diluent Oil, Carrier Fluid

ASTM Method	Description	Specification		
		Minimum	Maximum	Typical
	LB/GAL			7.07
D4052	Gravity, API			35.4
D445	Viscosity @ 40°C, cSt	9.00	10.00	9.29
D445	Viscosity @ 100°C, cSt			2.48
D2270	Viscosity Index	85		86
D92	Flash Point, °F (°C)	335 (168)		370 (188)
D5949	Pour Point, °C		-24	-30
D1500 or D6045	Color, ASTM		0.9	L0.9
D611	Aniline Point, °C			90
D7039	Sulfur, ppm		100	37
D1218	Refractive Index @ 20°C			1.4684
D2007	Hydrocarbon Type			
	Saturates, mass%			85.5
D3238	Carbon Distribution			
	% C_p			65.0
	% C_n			28.8
	% C_a			6.2
D6304	KF Moisture, ppm		100	

Mixing with incompatible chemicals may be hazardous. This product is intended for industrial use only. Safety data sheets are available upon request.

No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions®

www.amref.com

814-368-1200

