



# Kenwax<sup>®</sup> 0111

## Petrolatum

(C.A.S. #: 8009-03-8)

Product Code: P10-4459

Kenwax<sup>®</sup> 0111 – Petrolatum is a mixture of micro-crystalline wax and mineral oil. It is amber colored with a soft consistency and excellent cohesive properties.

### Kenwax<sup>®</sup> 0111 - Petrolatum

Bright Stock Petrolatum, 148 °F Melt Point Unrefined Petrolatum

**Applications:** Intermediate component in the production of cosmetics, lotions, ointments, etc.; water repellent/sealant used in the manufacture of particleboard and other woods; leather finishing; polishes; compounding of rubber; rust prevention; lubricants and more.

ASTM Method	Description	Specification		
		Minimum	Maximum	Typical
D1298B	Gravity, API			31.0
D92	Flash Point, °F	550		580
D88	Viscosity @ 155°F, cSt			49.0
D88	Viscosity @ 210°F, SUS	75.0	112.0	
D445	Viscosity @ 100°C, cSt	16.0	24.0	20.0
D127	Melt Point, °F	142	160	148
D937	Cone Pent. @ 77°F, dmm		100	60
D721	Oil Content, wt.%	8	15	10.5
	Sulfur, wt.%			0.04
D1500	Color, ASTM			8.0

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request.

No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions<sup>®</sup>

[www.amref.com](http://www.amref.com)

814-368-1200

