

# Grade No.1 Diesel

## S-15

(C.A.S. #: 64742-81-0)

Product Code: D10-8120

### Grade No.1 Diesel S-15

#1 ULSD Non-Road Dyed Red

ASTM Method	Description	Specification		
		Minimum	Maximum	Typical
D4052	Gravity, API	35.0		
D93	Flash, PMCC, °F	100		
D445	Viscosity @ 40°C, cSt	1.3	2.4	
D130	Copper Strip Corrosion		3.0	
D2622	Sulfur, % WT		0.0015	
D7039	Sulfur, mg/Kg		15.0	
D482	ASH, % Mass			NIL
D524	Rams. Carbon, % Mass			NIL
D5773	Cloud Point, °C (°F)		-15 (5)	-39 (-38)
D2709	Water & Sedi, Vol. %			NIL
D4737	Cetane Ind. (Calculated)	40		
D156	Color, Saybolt			27
D2624	Conduct., pS/m (C.U.)	25		
Method 15	Visual Inspection	Clear & Bright		
	Color (Dyed)	Red		
D86	Distillation, °F	IBP	325	351
		50%		398
		90% (From D975)	550	
		EBP		462

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request.

No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions®

www.amref.com

814-368-1200

