

# Kensol<sup>®</sup> 10

(C.A.S. #'s: 64742-48-9 & 68410-98-0)

Product Code: F10-4102

## Kensol<sup>®</sup> 10

Low Flash Naphtha, White Gas

**Applications:** Sport and Lantern Fuel, Rubber Solvent

ASTM Method	Description	Specification		
		Minimum	Maximum	Typical
	LB / GAL			5.90
D4052	Gravity, API	65		68
D5949	Pour Point, °C (°F)			-42 (-43.6)
D156	Color, Saybolt			+30
D86	Distillation, °F			
	IBP	100	135	
	10%	135	170	
	50%	200	235	
	95%	300	340	
	EBP		370	350
D4953	Reid Vapor Press., PSI	4.0	6.3	5.5
	Benzene Content, % WT			0.125
D130	Cu Strip Corrosion, (3 hrs @ 122°F)		1A	
D7039	Sulfur, ppm			<5
D4952	Doctor Test	Negative		

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request.

No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions<sup>®</sup>

[www.amref.com](http://www.amref.com)

814-368-1200

