

# Kensol<sup>®</sup> 30

(C.A.S. #: 8052-41-3)

Product Code: F10-4111

Regulatory: Vapor Pressure Meets the Requirements of Pennsylvania Code 025 Section 129.63 (a)4 for use in degreasing operations in cold cleaning machines. Vapor pressure also meets the requirements of New York codes, rules and regulations 6 NYCRR Part 226.3(a) 4 for use as a solvent in metal cleaning processes.

## Kensol<sup>®</sup> 30

Naphtha, Regular Mineral Spirits (RMS), Stoddard Solvent, 105°F Minimum Flash Point Mineral Spirits

**Applications:** Parts Cleaner, Paint Thinner, Charcoal Starter, Used in Hand Cleaners, Asphalt Cutbacks, Industrial Cleaners

ASTM Method	Description	Specification		
		Minimum	Maximum	Typical
	LB / GAL	6.40	6.47	6.43
D4052	Gravity, API	50.4	52.3	51.4
D56	Flash Point, °F (°C)	105 (41)		
D611	Aniline Point, °C			65
D1133	Kauri Butanol Value			32.52
D5949	Pour Point, °C (°F)			-60 (-76)
D2622	Sulfur, WT %		0.0050	<0.0005
D156	Color, Saybolt			+30
D86	Distillation, °F			
	IBP			310
	5%	310		322
	50%			341
	95%			375
	EBP		410	393
D1319	Flour. Indicator Analysis			
	Aromatics, Vol %			10.5
	Olefins, Vol %			0.4
	Saturates, Vol %			89.1

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request.

No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions<sup>®</sup>

www.amref.com

814-368-1200

