

Kendex® 2004H

(C.A.S. #: 64741-89-5)

Product Code: J10-4773

Kendex® 2004H

Specialty Blend

ASTM Method	Description	Specification		
		Minimum	Maximum	Typical
D4052	Gravity, API LB/GAL			34.6 7.093
D445	Viscosity @ 100°C, cSt	2.90	3.50	3.11
D445	Viscosity @ 40°C, cSt	11.00	14.50	11.40
D2270	Viscosity Index	115.0		128
D2983	Brookfield Vis @ -40°C	3000	6500	4500
D5949	Pour Point, °C (°F)			-51 (-60)
D92	Flash Point, °C, (°F)	154 (309)		177 (350)
D4951	Phosphorous, ppm	400	800	600
D4951	Zinc, ppm	300	500	425
D4172B – Mod.	Four Ball Wear – mm	0.32	0.42	0.36

Rev. 5/2015

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request.

No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions®

www.amref.com

814-368-1200

