

# Kendex® 0898

(C.A.S. #: 64742-16-1)

Product Code: L10-4618

## Kendex® 0898

Resins, Intermediate Resins, Intermediate Viscosity, Black, Sticky, Penn-Grade Resins

**Applications:** Viscosity Builder for Metalworking Applications

ASTM Method	Description	Specification		
		Minimum	Maximum	Typical
	LB/GAL			7.74
D1298A	Gravity, API			20.7
D445	Viscosity @ 40°C, cSt			3304
D2161	Viscosity @ 100°C, cSt	105.6	123.6	
D2270	Viscosity Index			95.0
D92	Flash Point, °F (°C)	600 (316)		630 (332)
D5949	Pour Point, °C			3
D1500	Color, ASTM			Opaque
D524	Ramsbottom Carbon Residue, %			3.25

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request.

No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions®

[www.amref.com](http://www.amref.com)

814-368-1200

