

Kendex[®] 0250

(C.A.S. #'s: 64742-54-7 & 64742-01-4)

Product Code: R10-4301

Kendex[®] 0250 is part of a family of process oil blends available in a variety of viscosity grades. These Kendex[®] blends are made using high quality, solvent dewaxed paraffinic base oils with naturally occurring high viscosity index, high flash, low pour point characteristics. They are ideally suited for use as components in a wide range of chemical blending and compounding operations, as diluent or carrier fluids, rubber process oils, plasticizers and in many other applications.

Kendex[®] 0250

Base Oil (Group I) Blend, Specialty Base Oil Blend

ASTM Method	Description	Specification		
		Minimum	Maximum	Typical
	LB/GAL			7.23
D4052	Gravity, API			31.5
D445	Viscosity @ 40°C, cSt	42.0	55.0	44.2
D445	Viscosity @ 100°C, cSt			6.68
D2270	Viscosity Index			103
D92	Flash Point, °F (°C)			400 (204)
D5949	Pour Point, °C (°F)		-9 (16)	-12 (10.4)
D1500	Color			3.5

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request.

No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions[®]

www.amref.com

814-368-1200

