

Kendex® 0842

(C.A.S. #: 64741-45-3)

Product Code: X07-4313

Kendex® 0842

Base Oil (Group I), Cylinder Stock

Applications: Asphalt Modifier, Metalworking Applications

ASTM Method	Description	Specification		
		Minimum	Maximum	Typical
	LB/GAL			7.53
D1298A	Gravity, API	23.0	27.0	25.0
D445	Viscosity @ 40°C, cSt			795
D445	Viscosity @ 65°C, cSt			170
D445	Viscosity @ 100°C, cSt	42	55	53
D2270	Viscosity Index			99.0
D92	Flash Point, °F (°C)	575 (302)		590 (310)
D5949	Pour Point, °C (°F)		24 (75.2)	
D524	Carbon Residue, (RAMS)			2.3
D611	Aniline Point, °C			128.5

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request.

No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions®

www.amref.com

814-368-1200

