

Kendex® 0846

(C.A.S. #: 64741-95-3)

Product Code: X07-4317

Kendex® 0846

Base Oil (Group I), Deresined Cylinder Stock

Applications: Cable Filler Component

ASTM Method	Description	Specification		
		Minimum	Maximum	Typical
	LB/GAL			7.43
D1298A	Gravity, API			26.0
D445	Viscosity @ 40°C, cSt			290
D445	Viscosity @ 65°C, cSt			99
D445	Viscosity @ 100°C, cSt	26.00	30.00	28.0
D2270	Viscosity Index			128
D92	Flash Point, °F (°C)	550 (288)		570 (299)
D5949	Pour Point, °C (°F)			27 (81)
D1500	Color, ASTM			Opaque
D189	Conradson Carbon Residue, %			1.03
D127	Drop Melt Point, °F			118.5
	% Oil Content			20-25

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request.

No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions®

www.amref.com

814-368-1200

