



Low Ash Stationary Gas Engine Oils

SAE 15W-40, SAE 30 and SAE 40

Low Ash Stationary Gas Engine Oils

Benefits:

- Utilize high quality paraffinic base oils for exceptional lubricity, film strength, low volatility and a high viscosity index
- Employ a proven, field tested additive system for superior engine protection and performance
- Offers excellent resistance to oxidation and nitration
- Protects against valve seat wear, cylinder and piston scuffing
- Provides improved deposit control and engine cleanliness.
- Contribute to reduced maintenance costs and longer engine life.
- Are suitable for use in engines using exhaust catalyst after - treatment (low phosphorous).
- Are available in three primary viscosity grades.

Applications:

- Designed for use in naturally aspirated and turbocharged four-stroke cycle natural gas engines
- Caterpillar 3500/3600, Waukesha 7077/7042, Dresser-Rand, Cooper-Superior, Cooper-Bessemer, Worthington and others where a low-ash gas engine oil is specified

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions®

www.amref.com

814-368-1200



SAE Grade	Test Method	15W-40	30	40
API Gravity, 60°F	ASTM D-4052	29.9	28.6	27.9
Density, lbs/gal (g/L)	Calculated	7.31 (875)	7.36 (882)	7.39 (886)
Viscosity, cSt @ 40°C	ASTM D-445	107.0	92.8	132.0
Viscosity, cSt @ 100°C	ASTM D-445	14.2	11.0	13.6
Viscosity Index	ASTM D-2270	132	102	98
Pour Point, °F (°C)	ASTM D-5949	-33 (-36)	-17 (-27)	-11 (-24)
CCS @ -20°C, cP	ASTM D-5293	6,300	N/A	N/A
MRV @ -25°C, cP	ASTM D-4684	26,000	N/A	N/A
Flash Point, °F (°C)	ASTM D-92	425 (218)	450 (232)	450 (232)
Color	ASTM D-1500	3.0	L 3.0	L 3.0
TBN	ASTM D-2896	5.2	5.2	5.2
Sulfated Ash, wt. %	ASTM D-874	0.45	0.45	0.45
Phosphorus, %wt.	Calculated	0.32	0.32	0.32
Product Code		7256	7257	7258

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions®

www.amref.com

814-368-1200

