



Bar & Chain Lubricant

Bar & Chain Lubricant

Benefits

- Fortified with extra tackifiers – helps minimize “fling off”
- Anti-wear agents and detergents protect nose sprocket and links
- Exceptional cold weather performance
- Provides better lubricating performance for mechanical and automatic link chains in both summer and winter applications

Applications:

- Chainsaws
- Motorcycles
- Farm equipment,
- Industrial equipment

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group, Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions®

www.amref.com

814-368-1200



Properties	Test Method	SAE 40
Gravity, API	ASTM D-4052	28.9
Density, lbs/gal (g/L)		7.36 (882)
Viscosity, cSt @ 40°C	ASTM D-445	118
Viscosity, cSt @ 100°C	ASTM D-445	13.5
Viscosity Index	ASTM D-2270	110
Color	ASTM D-1500	7.0
Pour Point, °F (°C)	ASTM D-5949	-22 (-30)
Flash Point, °F (°C)	ASTM D-92	425 (218)
QC Method #35 / Presence of Tackifier		Pass (Tacky/Stringy)
Product Code		7710