



Kendex[®] CAT

Description:

Kendex[®] CAT is a custom blend of aromatic extract oils obtained through a solvent-extraction process.

Recommended applications:

- Rubber-process oils industry
- Asphalt industry

<u>METHOD</u>	<u>SPECIFICATION</u>	<u>TYPICAL</u>
D-4052	API GRAVITY	14.0
D-4052	SPECIFIC GRAVITY, g/mL	0.9727
D-2501	VISCOSITY GRAVITY CONSTANT	0.9155
D-445	VISCOSITY at 40 °C, cSt	782.32
D-445	VISCOSITY at 100 °C, cSt	25.37
D-2270	VISCOSITY INDEX	-6
D-5949	POUR POINT, °C (°F)	9 (48)
D-92	FLASH POINT, °C (°F)	229 (445)
D-1500	COLOR	D8.0
D-2007	SATURATES, wt. %	31.34
D-1218	REFRACTIVE INDEX at -20 °C	1.55721
D-611	ANILINE POINT, °C	69.6
D-4294	SULFUR, ppm	3,931
<u>PRODUCT CODE</u>		4576

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied including patent warranties or warranties of merchantability or fitness for a particular purpose are made by American Refining Group Inc. with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



Specialty Refining Solutions[®]

www.amref.com
814-368-1200

