

#6 Fuel Oil

PROD. CODE
8201

As a high BTU content residual oil, #6 fuel oil powers waterborne vessels and is one of our many products designated for the marine industry's use.

FEATURES & BENEFITS

- Low sulfur

APPLICATION

Residual fuel, commercial/industrial boiler fuel, bunker fuel blend stock

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.73
D4052	API GRAVITY	16.0		21.3
	SPECIFIC GRAVITY @ 60°F			0.9260
D445	VISCOSITY @ 100°C, cSt			54.0
D92	FLASH POINT, °F (°C)	200 (93)		400 (204)
D2622	SULFUR, WT%		0.5	0.3
D5185	VANADIUM (V), ppm		10	<1.0
D5185	NICKEL (Ni), ppm		10	<1.0
D5185	SILICON (Si), ppm		100	<20
D5185	TITANIUM (Ti), ppm		1	<1.0
D5185	ALUMINUM (Al), ppm		50	<10

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

