

Kendex[®] 0060HT

PROD. CODE
4329

This light viscosity hydrotreated base oil is used in a variety of applications, including concrete form oils, carrier fluids, diluent oils and lubricant formulations.

FEATURES & BENEFITS

- Low sulfur
- High saturates
- Good thermal stability
- Improved oxidation stability

REGULATORY

Meets 21 CFR 178.3620(c) mineral oil as component of non-food articles intended for use in contact with food (FDA regulations)

APPLICATIONS

Lubricant formulations, diluent oils, carrier fluids, process oils, dust control, horticultural spray oils, spindle oil, concrete form oils

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.07
D4052	API GRAVITY			35.4
D92	FLASH POINT, °F	335		370
D5949	POUR POINT, °C		-15	-18
D7039	SULFUR, ppm		150	95
D611	ANILINE POINT, °C			90
D1500/D6045	COLOR, ASTM		1.0	L0.5
D445	VISCOSITY @ 40°C, cSt	9.00	10.00	9.29
D445	VISCOSITY @ 100°C, cSt			2.48
D2270	VISCOSITY INDEX	83.0		86.0
D1218	REFRACTIVE INDEX @ 20°C			1.4684
D2007	SATURATES, WT %			85.5
D3238	CARBON DISTRIBUTION			
	% C _p			65.0
	% C _n			28.8
	% C _a			6.2

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

 **AMERICAN
REFINING
GROUP, INC.**
Refine everything.™