

Kendex® 0150

PROD. CODE
4305

This 150 SN medium viscosity base oil is frequently used in a variety of lubricant applications including motor oils, hydraulic oils, tractor hydraulic fluids, gear oils, metalworking fluids and other industrial applications.

FEATURES & BENEFITS

- Good VI
- Excellent additive solubility
- Light color

REGULATORY

Meets 21 CFR 178.3620(c) mineral oil as a component of non-food articles intended for use in contact with food (FDA regulations)

APPLICATIONS

Motor oils, hydraulic oils, tractor hydraulic fluids, gear oils, metalworking fluids, lubricant formulations, process oils, manufacturing intermediates and other industrial applications

| METHOD | DESCRIPTION | SPECIFICATIONS | | |
|--------|------------------------|----------------|----------|-----------|
| | | MINIMUM | MAXIMUM | TYPICAL |
| | LBS/GAL | | | 7.21 |
| D4052 | API GRAVITY | | | 32.0 |
| D1500 | COLOR | | 3.0 | 1.5 |
| D445 | VISCOSITY @ 40°C, cSt | 27.0 | 32.0 | 30.0 |
| D445 | VISCOSITY @ 100°C, cSt | | | 5.2 |
| D2270 | VISCOSITY INDEX | 95.0 | | 100.0 |
| D92 | FLASH POINT, °F (°C) | 375 (191) | | 380 (193) |
| D5949 | POUR POINT, °F (°C) | | 10 (-12) | 5 (-15) |
| D5773 | CLOUD POINT, °C | | | -12.0 |

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

