

Kendex[®] 0150H

PROD. CODE
4315

This 150 neutral medium viscosity base oil is hydrodesulfurized for improved color and oxidation stability. It is used in a variety of lubricant applications, including motor oils, hydraulic oils, tractor hydraulic fluids, gear oils, metalworking fluids and other industrial applications.

FEATURES & BENEFITS

- Low sulfur
- Provides good VI
- Excellent solvency
- Low temperature fluidity

REGULATORY

Meets 21 CFR 178.3620(c) mineral oil as component of non-food articles intended for use in contact with food (FDA regulations)

APPLICATIONS

Motor oils, hydraulic oils, tractor hydraulic fluids, gear oils, metalworking fluids and industrial applications

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.21
D4052	API GRAVITY			32.0
D1500/D6045	COLOR		1.0	0.5
D445	VISCOSITY @ 40°C, cSt	27.0	32.0	
D445	VISCOSITY @ 100°C, cSt			5.2
D2270	VISCOSITY INDEX	95		102
D92	FLASH POINT, °F (°C)	380 (193)		425 (218)
D5949	POUR POINT, °C (°F)		-9 (16)	
D7039	SULFUR, ppm		300	200
D611	ANILINE POINT, °C			103
D2007	SATURATES, wt%			80
D130	COPPER STRIP CORROSION			1A

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

