

This high viscosity aromatic extract oil is used for industrial asphalt and rubber processing applications. It is sometimes referred to as a bright stock extract oil.

FEATURES & BENEFITS

- High aromatic content
- Enhances tire rubber formulations
- Rejuvenates aged asphalt

APPLICATIONS

Rejuvenator/modifier in paving asphalts, DAE in rubber process oils, used as a plasticizer in adhesives and coatings

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			8.3
D1298A	API GRAVITY			9.8
D92	FLASH POINT, °F	500		585
D445	VISCOSITY @ 100°C, cSt	100		130
D445	VISCOSITY @ 130°F, cSt			13,260
D2270	VISCOSITY INDEX		-50	-85
D5949	POUR POINT, °C			+27
D1500	COLOR			OPAQUE
D5948	RAMSBOTTOM CARBON RESIDUE			6.4

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

