

Kendex[®] 0897

PROD. CODE
4555

A light intermediate resin, this is primarily utilized as a viscosity builder in gear and wire rope lubricants, as well as the metalworking industry. This resin is black and highly viscous with almost no asphaltenes. It is also used in roofing asphalt.

FEATURES & BENEFITS

- Viscosity builder for lubricants
- Modifying agent for roofing asphalt

APPLICATIONS

Viscosity builder for metalworking applications; modifier for paving grade asphalt; used in roofing asphalt

METHOD	DESCRIPTION	SPECIFICATIONS		
		MINIMUM	MAXIMUM	TYPICAL
	LBS/GAL			7.62
D1298	API GRAVITY	21.9	24.5	23.6
D2161	VISCOSITY @ 100°C, cSt	40.0	75.0	57.8
D97	POUR POINT, °C		18	12
D92	FLASH POINT, COC, °F	575		580
D1500	COLOR, ASTM			OPAQUE

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

