

Used in industrial asphalt as a softening agent and rubber processes, the Kendex CAT customized specialty blend of aromatic extract oils is obtained during solvent extraction.

FEATURES & BENEFITS

- Modification agent for asphalt rejuvenation
- DAE in rubber process oils

APPLICATIONS

DAE in rubber process oils, asphalt industry

METHOD	DESCRIPTION	SPECIFICATIONS
		TYPICAL
D4052	API GRAVITY	14.0
D4052	SPECIFIC GRAVITY, g/mL	0.9727
D2501	VISCOSITY GRAVITY CONSTANT	0.9155
D445	VISCOSITY @ 40°C, cSt	782.32
D445	VISCOSITY @ 100°C, cSt	25.37
D2270	VISCOSITY INDEX	-6
D5949	POUR POINT, °C (°F)	9 (48)
D92	FLASH POINT, COC, °C (°F)	229 (445)
D1500	COLOR	D8.0
D2007	SATURATES, wt %	31.34
D1218	REFRACTIVE INDEX @ -20 °C	1.55721
D611	ANILINE POINT, °C	69.6
D4294	SULFUR, ppm	3,931

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

