

Used in asphalt modification/rejuvenation and rubber compounding. Kendex CAT is a customized specialty blend of aromatic extract oils and is produced through solvent extraction of Group I Base Oils.

## FEATURES & BENEFITS

- Modification agent for asphalt rejuvenation
- DAE in rubber process oils

## APPLICATIONS

DAE in rubber process oils, asphalt industry

		SPECIFICATIONS
METHOD	DESCRIPTION	TYPICAL
D4052	API GRAVITY	14.0
D4052	SPECIFIC GRAVITY, g/mL	0.9727
D2501	VISCOSITY GRAVITY CONSTANT	0.915
D445	VISCOSITY @ 40°C, cSt	782.3
D445	VISCOSITY @ 100°C, cSt	25.4
D2161	VISCOSITY @ 210°F, SUS	127
D2270	VISCOSITY INDEX	-6
D5949	POUR POINT, °C (°F)	9 (48)
D92	FLASH POINT, COC, °C (°F)	229 (445)
D1500	COLOR	D8.0
D2007	SATURATES, wt %	31.2
D1218	REFRACTIVE INDEX @ 20 °C	1.55721
D611	ANILINE POINT, °C	69.6
D4294	SULFUR, ppm	3,931
D4530	CARBON RESIDUE, MICRO METHOD wt %	5.5

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

