

This aromatic extract oil is utilized both in rubber compounding and as a rejuvenation compound for asphalt.

FEATURES & BENEFITS

- High aromatic content
- Enhances tire rubber formulations
- Rejuvenates aged asphalt

APPLICATIONS

Rejuvenator/modifier in paving asphalts, DAE in rubber process oils, used as a plasticizer in adhesives and coatings

METHOD	DESCRIPTION	SPECIFICATIONS
		TYPICAL
	LBS/GAL	7.74
D4052	API GRAVITY	21.1
	SPECIFIC GRAVITY	0.927
D445	VISCOSITY @ 40°C, cSt	51.45
D445	VISCOSITY @ 100°C, cSt	6.13
D2161	VISCOSITY @ 212°F, SUS	46.31
D2270	VISCOSITY INDEX	43
D5949	POUR POINT, °C	-18
D92	FLASH POINT, COC, °F (°C)	420 (216)
	MOLECULAR WEIGHT	366
D1218	REFRACTIVE INDEX, 20C	1.5240
D3238	% C IN AROMATICS	31.26
D3238	% C IN NAPHTHENICS	10.87
D3238	% C IN PARAFFINICS	57.87
D2007	SATURATES, %	50
D2887	BOILING BELOW 700°F, %	13

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

