American Refining Group, Inc.
Page 1 of 6

Revision Date: 11/9/2023
Revision #:2



Safety Data Sheet

Prepared according to GHS

1. Identification

Product Name Kenwax Heavy Neutral Slack Wax

Product Code 4454

Recommended Use Rust Preventatives, Hardboard manufacturing, fire logs

CompanyAmerican Refining Group, Inc. 77 North Kendall Avenue

Bradford, PA 16701 www.amref.com msds@amref.com

Emergency Telephone Chemtrec 1-800-424-9300 (24 HRS)

Number(s) ARG: 814-368-1297 (24 HRS)

2. Hazards Identification

GHS ClassificationThis product is not considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Signal WordNot applicableHazard StatementsNot applicableOther Hazard InformationNot applicableGHS PictogramNot applicable

3. Composition / Information on Ingredients

CAS No.	Component	Common Name	Percent	
This product does not contain ingredients that are hazardous by the OSHA Hazard Communication Standard				
(29 CFR 1910.1200)				

4. First Aid Measures

Eyes Check for and remove any contact lenses. Flush eyes with plenty of

water, occasionally lifting the upper and lower eyelids. Get

medical attention if irritation develops.

Skin In case of contact, immediately flush skin with plenty of soap and

water for at least 15 minutes while removing contaminated clothing

and shoes. Get medical attention if irritation develops.

Inhalation Move exposed person to fresh air. Get medical attention if

irritation develops.

Ingestion DO NOT INDUCE VOMITING. Seek medical attention

immediately.

Note to Physicians No specific treatment. Treat symptomatically. Contact poison

treatment specialist if large quantities have been ingested.

4454

5. Fire Fighting Measures

Revision Date: 11/9/2023

Revision #:2

Suitable Extinguishing Media

Use dry chemical, CO₂, water spray (FOG) or foam

Unsuitable Extinguishing Media

Avoid solid water stream as it may scatter and spread fire.

Specific Hazards Arising from Chemical

Elevated temperatures can lead to the formation of irritating fumes and vapors. Decomposing products may include the following materials: Carbon dioxide and Carbon monoxide.

Protective Equipment and Precautions for Firefighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental Release Measures

Personal Precautions

Put on appropriate personal protective equipment.

Environmental Precautions

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas.

Methods for Containment

Stop leak if without risk.

Methods for Cleanup

A vapor suppressing foam may be used to reduce vapors. Cover liquid spill with sand, earth or other noncombustible absorbent material. Cover powder spill with plastic sheet or tarp to minimize spreading. Pick up and transfer to properly labeled container

7. Handling and Storage

Handling Procedures

Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist.

Shipping and Storing Procedures

Keep container tightly closed in a dry place. Keep away from heat. Protect from light. Keep in properly labeled containers. Keep out of the reach of children.

Incompatibilities:

Oxidizing Agents

8. Exposure Controls / Personal Protection

Component Exposure Limits

Paraffin Wax Fume (8002-74-2)

 2 mg/m^3 **ACGIH TLV:** TWA: N/A ppm TWA: STEL: N/A ppm STEL: $N/A mg/m^3$ $N/A mg/m^3$ $N/A mg/m^3$ N/A ppm TWA STEL: N/A ppm STEL: **OSHA PEL:** TWA: 2 mg/m^3 $N/A mg/m^3$ **NIOSH REL:** TWA: N/A ppm TWA STEL: N/A ppm STEL:

N/A signifies not available

^{*}Product is a solid at 68°F and is not expected to present any inhalation hazard at ambient conditions. Caution should be when heating of this product. Paraffin wax fume, if generated, is considered hazardous according to the OSHA Hazard Communication Standard.

Kenwax Heavy Neutral Slack Wax Revision Date: 11/9/2023 American Refining Group, Inc.

Revision #:2 Page 3 of 6

8. Exposure Controls / Personal Protection

Engineering Controls

Material should be handled in enclosed vessels and equipment only if

heated. Use only in adequate ventilation if this occurs. Use process enclosures, local exhaust ventilation or other engineering controls to

keep worker exposure to airborne contaminants below any

recommended or statutory limits.

Eye/Face Protection Chemical goggles or face shield when heated to prevent hot wax thermal

burn.

Skin Protection Heat resistant, impervious gloves complying with an approved standard

should be worn at all times when product is heated to prevent hot wax

thermal burns.

Respiratory Protection No special requirements under ordinary conditions of use and with

adequate ventilation.

General Hygiene Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove

potentially contaminated clothing.

9. Physical and Chemical Properties

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Please see the Product Specification Sheet for further information.

Appearance	Cream or Tan	Flammability	Not Available
Physical State	Solid	Upper/Lower	Not Available
		Flammability Limits	
Odor	Bland	Vapor Pressure	Not Available
Odor Threshold	Not Available	Vapor Density	Not Available
pH	Not Available	Relative Density (lbs/gal)	7.11
Melting/Freezing Point	138/Not Available	Water Soluble	No
(°F)			
Initial Boiling Point (°F)	>600	Partition Coefficient: n-	3.3 to > 6
		octanol/water	
Boiling Range (°F)	Not Available	Auto-ignition	Not Available
		Temperature (°F)	
Flash Point (°F)	500	Decomposition	Not Available
		Temperature (°F)	
Evaporation Rate	Not Available	Viscosity (100°C mm²/s)	8.7 cSt
_		** product is expected to be solid at 40°C	

10. Chemical Stability & Reactivity Information

ReactivityPolymerization will not occurChemical StabilityStable under normal conditionsHazardous ReactionsNone, under normal processing.Conditions to AvoidHigh temperatures, flames, sparksIncompatibilityStrong acids and oxidizing materials

Hazardous Decomposition Smoke, carbon monoxide, carbon dioxide, aldehydes and other

Products products of incomplete combustion.

Revision Date: 11/9/2023 4454 Revision #:2 Page 4 of 6

11. Toxicological Information

Acute Exposure

Respiratory Irritation Not expected to pose respiratory irritation. An inhalation hazard may only

> arise if product is used in aerosol conditions or if heated up. If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and upper respiratory tract based upon data from

similar materials.

Not expected to cause irritation under normal use. **Eve Irritation Skin Irritation** Not expected to cause irritation under normal use. Sensitization Not expected to cause skin or respiratory sensitization. Not expected to pose an aspiration hazard if swallowed **Aspiration Hazards**

Chronic Exposure

Target Organ Effects No data available to indicate product or any components at greater than

1% are chronic health hazards.

Carcinogenicity This product contains mineral oils which are considered to be severely refined

> and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP

346 test.

Mutagenicity No data available to indicate product or any components present at greater

than

.1% are mutagenic or genotoxic.

No data available to indicate either product or components present at greater **Reproductive Toxicity**

than .1% that may cause reproductive toxicity.

No data available to indicate product or any components contained at greater **Teratogenicity**

than .1% may cause birth defects.

Analysis – LD50 / LC50

Inhalation LC50 Rat Not Available mg/L **Oral LD50 Rat** >5000 mg/kg**Dermal LD50 Rabbit** >3600 mg/kg

12. Ecological Information

Component Analysis- Ecotoxicity - Aquatic Life

Duration/Test/Species Concentration/Conditions

> >1000 mg/L96 hr LL50

Oncorhyncus mykiss

96 hr EL50 >1000 mg/L

Scenedesmus subspicatus

21 Day WAF 50% mg/L

Daphnia magna

Persistence & Degradability Inherently biodegradable

Bioaccumulation Potential Not Available Not Available **Soil Mobility Other Adverse Effects** Not Available

4454 Revision #:2 Page **5** of **6**

13. Disposal Considerations

Disposal Instructions

The generation of waste should be avoided or minimized wherever possible. Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

14. Transportation Information

Emergency Response Guide 171 North American Emergency Response

No. Guide Book

UN Number Shipping Name (technical Hazard Class Packing Group

name)

U.S. DOT Not Regulated

IATA Not Regulated

IMDG Not Regulated

STCC 2911990

15. Regulatory Information

SARA Extremely Hazardous This product does not contain greater than 1% of any "extremely hazardous substances" listed pursuant to Title III of the Superfund

Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

SARA Section 313 This product does not contain greater than 1.0% of the substances

subject to the reporting requirements of Section 313 of Title III of

the

Superfund Amendments and Reauthorization Act of 1986 and 40

CFR

Part 372.

SARA Section 311 & 312 Classifications Physical Hazards No

Health Hazards No.

CERCLA This product does not contain any "hazardous substances" listed under the

Comprehensive Environmental Response, Compensation and Liability Act of

1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

California Prop 65 This product is not routinely tested to determine chemical(s) known to the

state of California to cause cancer and/or birth defects based on maximum

impurity levels of components.

Kenwax Heavy Neutral Slack Wax 4454

Revision Date: 11/9/2023
Revision #:2

American Refining Group, Inc.
Page 6 of 6

Global Chemical Inventories

Global Chemical Inventories			
Inventory			
US TSCA	Listed		
EU	Listed		
Japan	Not available		
Australia	Listed		
New Zealand	Not Available		
Canada	Listed		
Switzerland	Not available		
Korea	Listed		
Philippines	Listed		
China	Listed		
Taiwan	Listed		

16. Other Information

US NFPA Ratings

Health	Fire	Reactivity
0	1	0

HMIS Ratings

Health	Fire	Physical Hazards
0	1	0

Revision Date 9 November 2023 **Revision Reason** Sections 9

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS