

ARGuard™ Automatic Transmission Fluid

PROD. CODE
7424

ARGuard™ Automatic Transmission Fluid is formulated with select base oils and additives to provide excellent oxidation control and low temperature performance required in passenger car and light duty truck transmissions manufactured prior to 2006.

FEATURES & BENEFITS

- Controls seal deterioration to limit fluid leakage
- Detergents/dispersant additives limit formulations of sludge and varnish deposits
- Provides excellent anti-wear protection for hydraulic pumps and power steering systems

INDUSTRY & OEM SPECIFICATIONS

- Dexron III H
- Ford Mercon
- Allison C-4
- Allison TES 389B

ARGuard™ Automatic Transmission Fluid is not intended for CVT transmissions, Dexron VI, or Ford Mercon LV applications

APPLICATIONS

ARGuard™ Automatic Transmission Fluid can be used in domestic and imported automatic transmission manufactured prior to 2006, certain off-highway power-shift transmissions, most power steering systems, and industrial and mobile hydraulic fluid systems

METHOD	DESCRIPTION	TYPICAL
Calculated	DENSITY, LBS/GAL	7.174
D4052	API GRAVITY	33.1
D445	VISCOSITY @ 40 °C, cSt	36.5
D445	VISCOSITY @ 100 °C, cSt	7.3
D2270	VISCOSITY INDEX	169
D2983	BROOKFIELD VIS at -40°C, cP	18,300
D5949	POUR POINT, °F (°C)	-54 (-48)
D92	FLASH POINT, °F (°C)	415 (213)

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



amref.com | 814.368.1200

